



## DECLARATION OF PERFORMANCE

No: KAGR\_004

1. Unique identification code of the product-type: **AQUAPANEL® Cement Board SkyLite SL\_8,0\_902**
2. Intended use/es: **AQUAPANEL® Cement Board 8 mm (hydrophobic) for use in suspended ceilings in interior and exterior applications.**
3. Manufacturer: **Knauf Aquapanel ABEE, 2nd Industrial Zone of Volos, GR – 37500 Volos**  
Tel.: +30 24250 24340, Fax: +30 24250 24342, E-Mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)
4. Authorised representative: not applicable
5. System/s of AVCP: **System 3, System 4**
6. a) Harmonised standard: not applicable  
Notified body/ies: not applicable
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body: **ETA-13/0608, Deutsches Institut für Bautechnik, 21.06.2013**  
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 13501-1
Board thickness	8,0 mm	ETA-13/0608
Apparent density (dry)	1230 ± 175 kg/m <sup>3</sup>	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski  
General Manager

Iserlohn, 25.01.2017

28.5.2014 L 159/43 Official Journal of the European Union EN

**AQUAPANEL®**

Be certain, choose AQUAPANEL®