



DECLARATION OF PERFORMANCE

No: KAGE_001

1. Unique identification code of the product-type: **AQUAPANEL® Cement Board Indoor**
ID_12,5_901, ID_12,5_903
2. Intended use/es: **AQUAPANEL® Cement Board Indoor is used for construction of indoor walls and ceilings especially in wet and humid areas.**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**
Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: aquapanel.info@knauf.com
4. Authorised representative: not applicable
5. System/s of AVCP: System 3 (reaction to fire), System 4 (all other product characteristics)
6. a) Harmonised standard: not applicable
Notified body/ies: not applicable
6. b) European Assessment Document: EAD 15-21-0024-05.04
European Technical Assessment: **ETA-07/0856**, dated 11.10.2017
Technical Assessment Body: Deutsches Institut für Bautechnik DIBt
Notified body/ies: MPA Nordrhein-Westfalen (0432) determined the reaction to fire classification
7. Declared performance/s:

| Essential Characteristics | Performance |
|--|--|
| Safety in case of fire (BWR 2) | |
| Reaction to fire | Class A1 according to EN 13501-1:2010-01 |
| Hygiene, health and environment (BWR 3) / Content, emission and/or release | |
| Vapour Permeability | μ = No performance assessed |
| Substance(s) classified as EU-cat. Carc. 1A/1B | The product does not contain these dangerous substances. |
| Substance(s) classified as EU-cat. Muta. 1A/1B | |
| Substance(s) classified as EU-cat. Acute Tox. 1, 2 and/or 3; substance(s) classified as EU-cat. Repr. 1A/1B; substance(s) classified as EU-cat. STOT SE 1 and/or STOT RE 1 | |
| SVOC and VOC | No performance assessed |
| Safety and accessibility in use (BWR 4) | |
| Thickness | $e = 12,5 \text{ mm} \pm 1,25 \text{ mm}$ |
| Dimensions (length and width) | Annex C |
| Straightness of edges | 0,1 % = Level I according to EN 12467 |
| Squareness of edges | 2 mm/m = Level I according to EN 12467 |

AQUAPANEL®



| Essential Characteristics | Performance | |
|--|--|-------------------------------------|
| Safety and accessibility in use (BWR 4) | | |
| Density | $\rho_{\text{mean}} = 1100 \pm 100 \text{ kg/m}^3$ | |
| Moisture content | $H = 8,0 \text{ \% by mass}$ | |
| Water permeability | Passed | |
| Dimensional stability – length | $\delta_{65,85} = 0,3 \text{ mm/m}$, $\delta_{65,30} = -0,3 \text{ mm/m}$ | |
| Dimensional stability – thickness | $\delta_{65,85} = 0,09 \text{ \%}$, $\delta_{65,30} = -0,06 \text{ \%}$ | |
| Bending strength | $f_{m,0,k} = 6,0 \text{ N/mm}^2$, $f_{m,90,k} = 6,3 \text{ N/mm}^2$ (smooth side under tension) $f_{m,90,k} = 5,9 \text{ N/mm}^2$ (smooth side under compression) | |
| Bending modulus of elasticity | $E_{m,0,\text{mean}}$, $E_{m,90,\text{mean}}$: No performance assessed | |
| Pull through resistance AQUAPANEL Maxi Screw | Type SN (Annex A1) | $f_{\text{head},k} = 280 \text{ N}$ |
| | Type SB (Annex A2) | $f_{\text{head},k} = 390 \text{ N}$ |
| Impact resistance | $IR_{\text{mean}} = 9,8 \text{ mm/m}$ | |
| Water adsorption | $w_a = 29,3 \text{ \% by mass}$ | |
| Warm water resistance for category C | $R_{L,ww} = 0,75$ | |
| Soak-dry resistance for category C | $R_{L,SD} = 0,98$ | |
| Durability of metal parts | Annex B1 | |
| Energy economy and heat retention (BWR 6) | | |
| Thermal conductivity | $\lambda_{10,1r} = \text{No performance assessed}$ | |
| Air permeability | The "AQUAPANEL Cement Board Indoor" is not permeable to air. | |

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski
General Manager

Iserlohn, 09.11.2018




28.5.2014 L 159/43 Official Journal of the European Union EN

AQUAPANEL®