



DECLARATION OF PERFORMANCE

No: KAGR_002

1. Unique identification code of the product-type: **AQUAPANEL® Cement Board Outdoor OD_12,5_902**
2. Intended use/es: **AQUAPANEL® Cement Board Outdoor is used for construction of suspended ceilings in outdoor applications and as lathing board in facades.**
3. Manufacturer: **Knauf Aquapanel ABEE, 2nd Industrial Zone of Volos, GR – 37500 Volos**
Tel.: +30 24250 24340, Fax: +30 24250 24342, E-Mail: aquapanel.info@knauf.com
4. Authorised representative: not applicable
5. System/s of AVCP: **System 3, System 4**
6. a) Harmonised standard: not applicable
Notified body/ies: not applicable
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body: **ETA-07/0173**
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 13501-1:2010-01
Board thickness	12,5 mm	ETA-07/0173
Apparent density (dry)	1150 ± 50 kg/m ³	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski
General Manager

Iserlohn, 09.06.2016



28.5.2014 L 159/43 Official Journal of the European Union EN



AQUAPANEL®