



## DECLARATION OF PERFORMANCE

No. KAQ\_0413

1. Unique identification code of the product-type: **AQUAPANEL® Joint Filler - grey**  
JFG\_131094\_001  
JFG\_131094\_012
2. Intended use/es: **Joint Filler for AQUAPANEL® Cement Board**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**  
Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)
4. Authorised representative: not applicable
5. System/s of AVCP: **System 4**
6. a) Harmonised standard: **EN 998-1:2016**  
Notified body/ies: not applicable
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body /  
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised tech. specification
Mortar class	General purpose mortar (GP) for interior and exterior use (CS IV)	EN 998-1:2016
Reaction to fire	A1	
Water absorption	W2	
Water vapour diffusion coefficient	$\mu = 5$ (wet cup); $\mu = 20$ (dry cup) table value EN 1745	
Adhesion	$\geq 0,07$ N/mm <sup>2</sup> , FP: B	
Thermal conductivity ( $\lambda_{10,dry}$ )	$\leq 0,45$ W/mK for P = 50%; $\leq 0,49$ W/mK for P = 90% (Table value EN 1745, dry density $\leq 1400$ kg/m <sup>3</sup> )	
Durability	NPD	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski, General Manager

Iserlohn, 06.08.2018

28.5.2014 L 159/43 Official Journal of the European Union EN

**AQUAPANEL®**