



AQUAPANEL®

08/2017

AQUAPANEL® SkyLite Reinforcing Mesh

Reinforcing mesh with alkali-resistant coating



Description

AQUAPANEL® SkyLite Reinforcing Mesh is an alkali-resistant glass fabric and it is used to reinforce AQUAPANEL® SkyLite Joint Filler & Skim Coating in exterior ceiling applications.

Technical data

Weight/unit area	approx. 125 g/m ²
Mesh size	4.1 x 4.1 mm
Initial tear strength	approx. 1,800 N/5 cm
Thickness	approx. 0.5 mm
Width	100 cm
Length	50 m
Colour	white

Processing

For exterior ceiling applications apply AQUAPANEL® SkyLite Joint Filler & Skim Coating 4 mm thick, spread to achieve a flat surface free from irregularities. Then embed the AQUAPANEL® SkyLite Reinforcing Mesh over the full surface, keeping it free of folds, close to the surface and with 10 cm joint overlaps.

Coverage

Approx. 1.10-1.15 m² per m² plastered surface

Working time

Ceiling area approx. 4-5 minutes/m²

Method of delivery/storage

- 100 cm wide rolls x 50 m long
- 35 Rolls / Pallet
- Store in a dry place and protect from moisture.

Item code: 475690

AQUAPANEL®

▶ www.AQUAPANEL.com

@ aquapanel.info@knauf.com

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany