

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Revision date: 15.07.2019  
Replacement of version 0018 of 14.07.2018

Version: 0019

# *Knauf Aquapanel GmbH & Co. KG*

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 *Product identifier*

Trade name **AQUAPANEL® Slot Adhesive (PU)**  
Product number **KAQ\_0435**  
Item code **110435**

### 1.2 *Relevant identified uses of the substance or mixture and uses advised against*

Appropriate use:  
The product is used as an adhesive (1C PUR mounting adhesive).

#### **Recommended restrictions on use:**

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.  
The conditions of restriction in accordance with Annex XVII of Regulation (EC) No 1907/2006 must be observed.

### 1.3 *Details of the supplier of the safety data sheet*

Knauf Aquapanel GmbH & Co. KG  
Zur Helle 11  
D-58638 Iserlohn

Telephone: +49-2374-50360      Fax: +49-2374-5036300  
e-mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)

e-mail-address of the competent person responsible for this Safety Data Sheet:  
[urban-finking.gefstoff@t-online.de](mailto:urban-finking.gefstoff@t-online.de)

#### **Technical contact:**

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn  
Telephone: +49-2374-50360      Fax: +49-2374-5036300

### 1.4 *Emergency telephone number*

Giftnotruf Berlin, Advice in German and English  
Telephone: +49-30-30686 790  
(24 hours, Monday – Sunday)

## SECTION 2: Hazards identification

### 2.1 *Classification of the substance or mixture*

Skin Irrit. 2; H315  
Skin Sens. 1; H317  
Eye Irrit. 2; H319  
Resp. Sens. 1; H334  
STOT SE 3; H335  
Carc. 2; H351  
STOT RE 2; H373  
Aquatic Chronic 3; H412

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

**2.2 Label elements**

Hazard pictogram(s):



Signal word(s):

Danger

Product identifier:

AQUAPANEL® Slot Adhesive (PU)  
contains polymethylene polyphenyl isocyanate,  
methylenediphenyl diisocyanate, mixture of isomers

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P102	Keep out of reach of children.
P260	Do not breathe mist/vapours.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

Supplemental hazard information:

EUH204 Contains isocyanates. May produce an allergic reaction.

**Conditions of restriction in accordance with Annex XVII of Regulation (EC) No 1907/2006:**

No 56 methylenediphenyl diisocyanate (MDI):

**Demands on packaging for supply to the general public:**

- The packaging must contain protective gloves which comply with the requirements of Directive 89/686/EEC.
- The packaging must be marked visibly, legibly and indelibly as follows:  
Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.  
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**Remarks:**

- According to Article 35 paragraph 2 of Regulation (EC) No 1272/2008 packaging supplied to the general public should not have either a shape or form to mislead consumers.
- According to Annex II section 3.2 of Regulation (EC) No 1272/2008 the packaging containing this mixture and the general public shall be fitted with a tactile warning of danger.
- The use of the precautionary statements P102 and P501 is necessary for the labelling of the dangerous mixture supplied to the general public.

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

**2.3 Other hazards**

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.  
 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 The mixture does not contain any substances classified as PBT/vPvB in a concentration of 0.1% or more.

**SECTION 3: Composition/information on ingredients**
**3.2 Mixtures**

REACH registration number:  
 - Polymethylene polyphenyl isocyanate: 01-2119457024-46-0000  
 - Methylene-diphenyl diisocyanate: 01-2119457015-45-XXXX  
 - Diethylmethylbenzenediamine: 01-2119486805-25-XXXX

**Characterisation**

This product is a mixture. It is a solution of isomers of methylenediphenylmethane diisocyanate, diethylmethylbenzenediamine and specific components.

**Substances presenting a health/environmental hazard within the meaning of Regulation (EC) No 1272/2008**

CAS No	EC No	Identification	% by weight	Classification
9016-87-9	not available	polymethylene polyphenyl isocyanate	30 - < 39	Carc. 2; H351 STOT RE 2; H373 STOT SE 3; H335 Resp. Sens. 1; H334 Skin Sens. 1; H317 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319
26447-40-5	247-714-0	methylenediphenyl diisocyanate	10 - 16	Carc. 2; H351 STOT RE 2; H373 STOT SE 3; H335 Resp. Sens. 1; H334 Skin Sens. 1; H317 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319
68479-98-1	270-877-4	diethylmethylbenzenediamine	< 0.5	Acute Tox. 4; H302 Acute Tox. 4; H312 STOT RE 2; H373 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

See subsection 2.2 for further details. Full text of the hazard statements see Section 16.

**Substances for which Union workplace exposure limits have been assigned (see also Section 8.)**

No substances.

**Additional information**

Specific concentration limits for polymethylene polyphenyl isocyanate and methylenediphenyl diisocyanate:

Resp. Sens. 1: C ≥ 0.1%  
 STOT SE 3: C ≥ 5%  
 Eye Irrit. 2: C ≥ 5%  
 Skin Irrit. 2: C ≥ 5%

Trade name: AQUAPANEL® Slot Adhesive (PU)

Product number: KAQ\_0435

Company/Undertaking: Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn

Telephone: +49-(0)2374-50360

Revision date: 15.07.2019

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Remove contaminated, soaked clothing immediately and dispose of safely.  
In the immediate working surroundings emergency shower and eye wash must be installed.  
Label their location conspicuously.

#### In case of inhalation

Take affected person to fresh air.  
When vapours are inhaled, poisonous symptoms can first be observed after several hours, therefore it is essential to consult a doctor.

#### In case of contact with skin

In case of contact with skin wash off immediately with polyethylene glycol 400.  
Subsequently wash again with soap and water. Avoid drying of product on the skin absolutely.  
Consult a doctor if skin irritation persists.

#### In case of contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do.

#### In case of ingestion

Rinse mouth immediately. Spit out liquid immediately.  
Do not induce vomiting. Take medical treatment immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Asthmatic complaints. Allergic symptoms. Risk of respiratory disorders.  
Possibility of temporary symptoms such as coughing, headache and nausea.  
Irritating to respiratory tract, eyes, gastro-enteric tract and skin.

### 4.3 Indication of any immediate medical attention and special treatment needed

Poisonous symptoms can first be observed after several hours, therefore medical observation for at least 48 hours is necessary.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam, carbon dioxide, dry powder, water spray jet.

#### Unsuitable extinguishing media

Full water jet.

### 5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released: nitrous gases, carbon monoxide, carbon dioxide, isocyanate vapours, traces of hydrogen cyanide.

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus. Wear chemical resistant suit.  
Do not inhale explosion and/or combustion gases. Cool endangered containers with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

## SECTION 6: Accidental release measures

### 6.1 *Personal precautions, protective equipment and emergency procedures*

#### **For non-emergency personnel**

Use personal protective clothing. Ensure adequate ventilation. Keep away from unprotected people.  
Use breathing apparatus if exposed to vapours/aerosol. Keep away sources of ignition.

#### **For emergency responders**

For suitable fabric for personal protective clothing see Section 8.

### 6.2 *Environmental precautions*

Do not discharge into the drains, the aquatic environment and soil.

### 6.3 *Methods and material for containment and cleaning up*

Cover with wet binding agent (e.g. clay, diatomaceous earth, sand, sawdust).  
Collect in appropriate containers after approx. 1 hour.

Cover container, but do not close container due to possible evolution of CO<sub>2</sub>.

Allow waste material to react for several days. Send containers for disposal.

Product hardens in contact with water. Clear contaminated area thoroughly with plenty of water.

### 6.4 *Reference to other sections*

For personal protective equipment see also Section 8.

For disposal considerations see also Section 13.

## SECTION 7: Handling and storage

### 7.1 *Precautions for safe handling*

#### **Advice on safe handling**

Open and handle container with care. Avoid contact with skin and eyes.

Avoid formation of vapours/aerosols. After use containers must be resealed.

Provide good ventilation of working area (local exhaust ventilation if necessary).

In case of open handling equipment with built-in suction must be used.

If suction of the immediate vicinity is impossible or insufficient, the entire working place must be sufficiently ventilated using appropriate machines.

Comply with the minimum standards in accordance with TRGS 500<sup>1</sup> and with the protective measures in accordance with TRGS 401<sup>1</sup> and TRGS 430<sup>1</sup>.

#### **Inhalation:**

In designing the work process the model solutions of the Control Guidance Sheets 100<sup>1</sup> and 110<sup>1</sup> must be taken into consideration in case of possible release of only small amounts of product (range of grams).

In designing the work process the model solutions of the Control Guidance Sheet 200<sup>1</sup> must be additionally taken into consideration in case of possible release of medium to large amounts of product (range of kilograms up to tons).

#### **Skin contact:**

In designing the work process the model solutions of the Control Guidance Sheets 120<sup>1</sup> and 250<sup>1</sup> must be taken into consideration in case of small-area skin contact (e.g. splashes) and regardless on the duration of skin contact.

In case of large-area skin contact (wetting of the skin) and short-term effect (duration of skin contact less than 15 minutes per shift), the model solutions of the Control Guidance Sheets 120<sup>1</sup> and 250<sup>1</sup> must be taken into

consideration as well. In case of long-term effect (duration of skin contact more than 15 minutes per shift), the model

solutions of the Control Guidance Sheet 300<sup>1</sup> (closed system) must be additionally taken into consideration.

#### **Advice on general occupational hygiene**

Do not inhale vapours and aerosols. Avoid contact with eyes and skin.

Avoid drying of product on the skin absolutely.

Change soiled or soaked clothing immediately. Store work clothing separately.

At work do not eat, drink, smoke or take drugs. Storage of foodstuffs in work rooms is forbidden.

After worktime and before breaks the affected skin areas must be thoroughly cleaned.

After work protect skin by using skin protective cream. Set out skin protection guidelines.

In the immediate working surroundings emergency shower and eye wash must be installed.

Label their location conspicuously.

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Revision date:	15.07.2019
Telephone:	+49-(0)2374-50360		

**7.2 Conditions for safe storage, including any incompatibilities**

**Advice on protection against fire and explosion**

Keep away sources of ignition.

**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully.  
Keep only in the original container. Protect container from direct sunlight.

**Advice on storage compatibility**

Do not store together with oxidising agents, strong acids and strong alkalis.  
The information about joint storage given in Table 2 of TRGS 510<sup>1</sup> must be observed.

**Further information on storage conditions**

Do not keep at temperatures above 50°C and below +5°C.  
Maximum period of storage (time): unopened storage life approx. 15 months.  
Recommended storage temperature between 15 and 25°C.

**Storage class (for Germany only)**

LGK 10 (combustible liquids unless classified in storage class 3) in accordance with TRGS 500<sup>1</sup>.

**7.3 Specific end use(s)**

The product is only intended for the uses mentioned under subsection 1.2. Observe technical data sheet.  
GISCODE<sup>4</sup>: RU 1 (solvent-free polyurethane installation products)

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

CAS No	Identification	Limit values	Remarks
9016-87-9	polymeric MDI (calculated as MDI)	0.05 mg/m <sup>3</sup> inhalable aerosol  0.05 (15 minutes average value) 0.1 (ceiling limit value)	<b>National limit values – eight hours</b> Germany <b>National limit values – short term</b> Germany
101-68-8	diphenylmethane-4,4'- diisocyanate	0.05 mg/m <sup>3</sup> 0.052 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> inhalable aerosol and vapour 0.05 mg/m <sup>3</sup> 0.02 mg/m <sup>3</sup> as NCO 0.05 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 0.002 mg/m <sup>3</sup> 0.052 mg/m <sup>3</sup> 0.03 mg/m <sup>3</sup>  0.1 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 0.2 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> inhalable aerosol and vapour 0.05 mg/m <sup>3</sup> 0.07 mg/m <sup>3</sup> as NCO 0.1 mg/m <sup>3</sup> 0.2 mg/m <sup>3</sup> 0.15 mg/m <sup>3</sup> 0.03 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup>	<b>National limit values – eight hours</b> Austria Belgium Czech Republic Denmark Estonia France Germany  Hungary Ireland Lithuania Poland Slovakia Spain Sweden <b>National limit values – short term</b> Austria Czech Republic Denmark Estonia France Germany  Hungary Ireland Lithuania Poland Romania Slovakia Sweden

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

(continued from 8.1 Control parameters)

CAS No	Identification	Limit values	Remarks
26447-40-5	diphenylmethane diisocyanate (all isomers)	0.03 mg/m <sup>3</sup>	<b>National limit values – eight hours</b> Poland
		0.09 mg/m <sup>3</sup>	<b>National limit values – short term</b> Poland
		0.15 mg/m <sup>3</sup>	Romania

**Additional limit values for polymethylene polyphenyl isocyanate in accordance with the registration dossier:**

- **DNEL (Derived No-Effect Level)**
  - workers, long term exposure: inhalation, local effects: 0.05 mg/m<sup>3</sup>
  - workers, short term exposure: inhalation, local effects: 0.1 mg/m<sup>3</sup>
  - general population, long term exposure: inhalation, local effects: 0.025 mg/m<sup>3</sup>
  - general population, short term exposure: inhalation, local effects: 0.05 mg/m<sup>3</sup>
- **PNEC (Predicted No-Effect Concentration)**
  - aquatic, freshwater: 1 mg/l
  - aquatic, marine water: 0.1 mg/l
  - aquatic, freshwater, intermittent release: 10 mg/l
  - aquatic, sewage treatment plant: 1 mg/l
  - soil environment: 1 mg/kg<sub>dw</sub>

**Additional limit values for diphenylmethane-4,4'-diisocyanate in accordance with the registration dossier:**

- **DNEL (Derived No-Effect Level)**
  - workers, long term exposure: inhalation, local effects: 0.05 mg/m<sup>3</sup>
  - workers, short term exposure: inhalation, local effects: 0.1 mg/m<sup>3</sup>
  - general population, long term exposure: inhalation, local effects: 0.025 mg/m<sup>3</sup>
  - general population, short term exposure: inhalation, local effects: 0.05 mg/m<sup>3</sup>
- **PNEC (Predicted No-Effect Concentration)**
  - aquatic, freshwater: 1 mg/l
  - aquatic, marine water: 0.1 mg/l
  - aquatic, freshwater, intermittent release: 10 mg/l
  - aquatic, sewage treatment plant: 1 mg/l
  - soil environment: 1 mg/kg<sub>dw</sub>

**Additional limit values for diethylmethylbenzenediamine in accordance with the registration dossier:**

- **DNEL (Derived No-Effect Level)**
  - workers, long term exposure: inhalation, systemic effects: 0.13 mg/m<sup>3</sup>
  - workers, long term exposure: dermal, systemic effects: 1 mg/kg<sub>bw/d</sub>
  - general population, long term exposure: inhalation, systemic effects: 0.1 mg/m<sup>3</sup>
  - general population, long term exposure: dermal, systemic effects: 1 mg/kg<sub>bw/d</sub>
  - general population, long term exposure: oral, systemic effects: 0.1 mg/kg<sub>bw/d</sub>
- **PNEC (Predicted No-Effect Concentration)**
  - aquatic, freshwater: 0.001 mg/l
  - aquatic, marine water: 0 mg/l
  - aquatic, freshwater, intermittent release: 0.005 mg/l
  - aquatic, sewage treatment plant: 17 mg/l
  - sediment, freshwater: 0.029 mg/kg<sub>dw</sub>
  - sediment, marine water: 0.003 mg/kg<sub>dw</sub>
  - soil environment: 0.0056 mg/kg<sub>dw</sub>
  - secondary intoxication, food, oral: 2 mg/kg food

The methods for measuring chemical agents in workplace atmosphere must meet the general requirements of EN 481, EN 482 and EN 689.

## 8.2 Exposure controls

### Appropriate engineering controls

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See also subsection 7.1.

The protective measures in accordance with TRGS 430<sup>1</sup> must be taken into consideration.

The effectiveness of suitable protective measures must be controlled.

Suitable assessment methods are described in the German TRGS 402<sup>1</sup>.

### Individual protection measures, such as personal protective equipment

Personal protective equipment needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer/supplier of the personal protective equipment.

#### Eye/face protection



Tightly fitting safety glasses in accordance with EN 166 (e.g. eye glasses with side shields).

#### Hand protection



The protective gloves to be used must comply with the specifications of the standard EN 374.

Suitable material:

Butyl rubber; thickness 0.7 mm; permeation time: level 6 (≥ 480 minutes).

Nitrile rubber; thickness 0.4 mm; permeation time: level 6 (≥ 480 minutes).

Natural rubber; thickness 0.5 mm; permeation time: level 6 (≥ 480 minutes).

Wear cotton gloves underneath protection gloves if possible.

Under practical conditions, the maximum wearing period can be significantly lower.

Suitable gloves for the handling of solvent-free polyurethane installation products (GISCODE<sup>4</sup>: RU1) in accordance with GISBAU (Information system of the the German professional associations for building and construction industry):

- ANSELL: Sol-Vex, Butyl Plus R
- Ampri: SolidSafety ChemP 081301, SolidSafety ChemP Thermo 081302, SolidSafety ChemN 081003, Clean Expert Nitril 01166
- KCL: Camatril, Butojet 897/898, Camapren 720/722, Dura Nit, Vitojet, Combi Latex 395/403, Trikotil K, Trikotil Winter, Tricopren, Camatril Velour, Tricotril 736/737
- MAPA: Ultranitil 480 / 492 / 493, Fluotex 344, Fluonit 468, TopChem 345, Butoflex 650/651
- UVEX: UVEX Rubiflex B, UVEX Rubiflex S, UVEX Profastar, UVEX Profastrong, UVEX Profapren, UVEX Profapren S, UVEX Profabutyl, UVEX Profaviton

The protective gloves to be used must comply with the specifications of the standard EN 374.

#### Body protection

Closed work clothing.

#### Respiratory protection



In case of spraying, higher concentrations and if ventilation insufficient, use suitable respiratory protection, i.e. full mask/half mask/filtering half mask with

- combination filter A-P2
- combination filter B-P2.

The limitations in wearing time according to the DGUV Regel 112-190<sup>2</sup> (rule of the German employers' liability insurance association) for the use of respirators have to be observed.

#### Thermal hazards

Not relevant.

#### Environmental exposure controls

See Section 6.



Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	pasty
Colour:	beige, grey
Odour:	characteristic
Odour threshold:	no data available
pH (as supplied):	not relevant
pH (of an aqueous solution):	not relevant
Melting point/freezing point (°C):	not determined
Boiling point and boiling range (°C):	not determined
Flash point (°C), closed cup:	> 200 (information of the manufacturer)
Evaporation rate:	not determined
Flammability (solid, gas):	not relevant
Upper flammability or explosive limit:	not determined
Lower flammability or explosive limit:	not determined
Vapour pressure (20°C) (mbar):	no data available
Vapour density (20°C):	no data available
Relative density:	no data available
Density (g/cm³):	approx. 1.45
Solubility in water:	water-insoluble; decomposition (polymerisation)
Soluble in:	not determined
Partition coefficient: n-octanol/water:	no data available
Auto-ignition temperature (°C):	not relevant
Decomposition temperature (°C):	no data available
Viscosity (20°C):	thixotropic
Explosive properties:	not explosive
Oxidising properties:	not relevant

### 9.2 Other information

None.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product reacts with water (hydrolysis).

### 10.2 Chemical stability

The product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

At elevated temperatures and in contact with tertiary amines and organic tin compounds, technical MDI and monomeric diphenylmethane-4,4'-diisocyanate can polymerise under intense heat.

### 10.4 Conditions to avoid

Exposure to moisture may cause evolution of carbon dioxide and overpressure can occur in containers (risk of bursting).

### 10.5 Incompatible materials

Under normal conditions diphenylmethane diisocyanate reacts slowly with water, with evolution of carbon dioxide (formation of excessive pressure in sealed containers).  
Exothermic reaction with amines, alcohols, strong acids, strong alkalis and oxidising agents.

### 10.6 Hazardous decomposition products

Carbon dioxide.  
For hazardous combustion products see subsection 5.2.

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

No data are available for the product.

#### Acute toxicity

LD50 rat, oral	(mg/kg)	> 2000	(polymethylene polyphenyl isocyanate)	(OECD Test Guideline 401)
		> 7616	(diphenylmethane-4,4'-diisocyanate)	(OECD Test Guideline 401)
		472	(diethylmethylbenzenediamine)	(RTECS)
LD50 rabbit, dermal	(mg/kg)	> 9400	(polymethylene polyphenyl isocyanate)	(OECD Test Guideline 402)
		> 9400	(diphenylmethane-4,4'-diisocyanate)	(OECD Test Guideline 402)
		> 2000	(diethylmethylbenzenediamine)	(OECD Test Guideline 402)
LC50 rat, inhalation	(mg/l/4h)	0.49	(polymethylene polyphenyl isocyanate)	(OECD Test Guideline 403)
		0.49	(diphenylmethane-4,4'-diisocyanate)	(OECD Test Guideline 403)

#### Skin corrosion/irritation

Irritant effect on skin (rabbit)	Irritating	(polymethylene polyphenyl isocyanate)	(OECD Test Guideline 404)
	Irritating	(diphenylmethane-4,4'-diisocyanate)	(OECD Test Guideline 404)

#### Serious eye damage/irritation

Irritant effect on eyes	Mild eye irritation on eyes of rabbits (dose: 100 mg)	(RTECS)
	(Standard Draize Test; polymethylene polyphenyl isocyanate)	
	Mild eye irritation on eyes of rabbits (dose: 100 mg)	(RTECS)
	(Standard Draize Test; diphenylmethane-4,4'-diisocyanate)	

#### Respiratory or skin sensitisation

The product contains polymethylene polyphenyl isocyanate and methylenediphenyl diisocyanate (mixture of isomers). These components are classified as sensitising by inhalation and skin contact.

#### Germ cell mutagenicity

The mixture does not contain substances classified as germ cell mutagens.

#### Carcinogenicity

Polymethylene polyphenyl isocyanate and respirable aerosols of diphenylmethane-4,4'-diisocyanate are suspected to cause cancer in accordance with the German TRGS 905 (category K2). Suspected of causing cancer.

#### Reproductive toxicity

The mixture does not contain substances classified as toxic for the reproduction.

#### Specific target organ toxicity (STOT)-single exposure

May cause respiratory irritation.

#### Specific target organ toxicity (STOT)-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

The mixture does not contain aspiration toxicants.

#### Symptoms related to the physical, chemical and toxicological characteristics

Asthmatic complaints. Allergic symptoms. Risk of respiratory disorders.  
Possibility of temporary symptoms such as coughing, headache and nausea.  
Irritating to respiratory tract, eyes, gastro-enteric tract and skin.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Very low concentrations of methylenediphenyl diisocyanate may cause allergic reactions in sensitive persons. Those persons may not have any further contact with this substance.  
Complaints can first be observed after several hours or days (bronchial asthma due to vapours of methylene-diphenyl diisocyanate and allergic symptoms).

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

96 h LC50	(fish)	> 1000 mg/l	(Danio rerio; zebrafish)	(OECD Test Guideline 203)
			(polymethylene polyphenyl isocyanate)	
		> 1000 mg/l	(Danio rerio; zebrafish)	(OECD Test Guideline 203)
			(diphenylmethane-4,4'-diisocyanate)	
48 h EC50	(daphnia)	0.5 mg/l	(Daphnia magna)	(EU method C2)
			(diethylmethylbenzenediamine)	
72 h IC50	(algae)	> 1640 mg/l	(Desmodesmus subspicatus; green algae)	
			(polymethylene polyphenyl isocyanate)	
			(OECD Test Guideline 201)	
		> 1640 mg/l	(Desmodesmus subspicatus; green algae)	
			(diphenylmethane-4,4'-diisocyanate)	
			(OECD Test Guideline 201)	

#### Behaviour in sewage works:

The behaviour of the product in sewage treatment plants has not been tested. Do not discharge into the drains.

### 12.2 Persistence and degradability

Under normal conditions diphenylmethane diisocyanate reacts slowly with water, with evolution of carbon dioxide and formation of solid polyurea (insoluble, not biodegradable and not acute toxic).

Chemical oxygen demand (COD)	No data available.
Biochemical oxygen demand (BOD5)	No data available.
AOX-hint	Not to apply.

### 12.3 Bioaccumulative potential

The product has not been tested.

### 12.4 Mobility in soil

The product has not been tested.

### 12.5 Results of PBT and vPvB assessment

The mixture does not contain any substances classified as PBT/vPvB in a concentration of 0.1% or more.

### 12.6 Other adverse effects

Ozone depletion potential	No data available.
Photochemical ozone creation potential	No data available.
Global warming potential	No data available.

Product reacts with water, with evolution of carbon dioxide.

The product is classified as slightly hazardous to water.

**Contains according to the formulation following heavy metals and compounds of EC-Directives 2006/11/EC and 80/68/EEC:**

None.

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Revision date:	15.07.2019
Telephone:	+49-(0)2374-50360		

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste disposal according to official state regulations.  
Consult the local waste disposal expert about waste disposal.  
Sewage disposal must be avoided.

#### Disposal operations/recovery operations according to Directive 2008/98/EC

Disposal operations:	D 10	Incineration on land
Recovery operations:	R 1	Use principally as a fuel or other means to generate energy

#### Properties of waste which render it hazardous in accordance with Annex III of Directive 2008/98/EC

HP 4:	Irritant
HP 5:	Specific Target Organ Toxicity (STOT)
HP 7:	Carcinogenic
HP 13:	Sensitising
HP 14:	Ecotoxic

#### Product/unused product

Waste disposal corresponding to European Waste Catalogue. Wastes must be classified with respect to their origin and depending on different processing steps. The waste codes mentioned as follows are only constituted as our recommendations. Referring to the particular case they should be completed or revised.

EC waste code:	08 04 09
Waste notation:	Waste adhesives and sealants containing organic solvents or other hazardous substances

#### Contaminated packaging

Recommendation:	Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Recommended cleansing agent:	No information available.
Packaging that cannot be cleaned:	
EC waste code:	15 01 10
Waste notation:	Packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in accordance with the UN Model Regulations (ADR/RID/ADN/IMDG/ICAO/IATA).

### 14.2 UN proper shipping name

Not relevant.

### 14.3 Transport hazard class(es)

Not relevant.

### 14.4 Packing group

Not relevant.

### 14.5 Environmental hazards

Not relevant.

### 14.6 Special precautions for user

Not relevant.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not relevant.

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Information regarding relevant Union safety, health and environmental provisions

Regulation (EC) No 1907/2006: Annex XVII, No 56  
(methylenediphenyl diisocyanate (MDI))

Observe employment restrictions under the law for the protection of young people at work (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

#### Information regarding national laws/national measures that may be relevant (for Germany only)

Restriction of occupation: Law for the protection of expectant and nursing mothers; Youth Employment Protection Act must be observed.

Major-accident Ordinance: Not relevant  
Fire and explosion hazards: Not relevant  
Regulation on clean air (TA Luft): Number 5.2.5, class I, diphenylmethane diisocyanate (MDI) – slightly hazardous to water (deduction of the WGK according to Annex 1 No 5.2 AwSV)<sup>3</sup>  
Water hazard class: The German Ordinance on facilities for handling substances that are hazardous to water (AwSV) has to be observed.

German Ordinance on Hazardous Substances (in accordance with EC-Directive 98/24/EC): Articles 7, 8, 9, 14  
Regulation on Occupational Medical Prevention (ArbMedVV):

Annex, Part 1 (1):  
**Obligatory prophylaxis:** The employer shall arrange occupational medical prophylaxis for workers conducting activities with exposure to this substance, when frequent skin contact cannot be excluded or the air concentration exceeds 0.05 milligrams per cubic meter.

Annex, Part 2 h.):  
**Prophylaxis offer:** Occupational medical prevention has to be offered, when activities with exposure to this substance are conducted whereby an air concentration of 0.05 mg per cubic meter is observed or skin contact cannot be excluded.

Technical Rules for Hazardous Substances<sup>1</sup>: TRGS 400, 401, 402, 406, 430, 500, 510, 555, 600, 900, 905

Rules of the employers' liability insurance association<sup>2</sup>: DGUV Regel 112-189, 112-190, 112-192, 112-195

Information of the employers' liability insurance association<sup>2</sup>: DGUV Information 250-429

Classification in accordance with the easy-to-use workplace control scheme for hazardous substances of the Federal Institute for Occupational Safety and Health, version 2.2, 2014<sup>5</sup>:  
inhalation: hazard group C  
skin contact: hazard group HD  
(the protective measures in accordance with TRGS 430<sup>1</sup> should be applied preferably)

In accordance with Article 16e of the German Chemicals Act there is an obligation to notify the product at the Federal Institute of Risk Assessment (BfR).

Number of the product in the Poison Information Database: 5712629

### 15.2 Chemical safety assessment

No chemical safety assessment has been carried out for a substance in the product.

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

**SECTION 16: Other information**

**Keeping (restrictions)** Article 8 paragraphs 5 and 6 of the German Ordinance on Hazardous Substances has to be observed. (only for Germany)

**Supply** to industry consumer, to the general public

**Full text of the hazard statements referred to under subsections 2.1 and 3.2 of the Safety Data Sheet**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Key to abbreviations and acronyms used in the safety data sheet**

ADN:	Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ADR:	Accord européen relatif au transport international des marchandises dangereuses par route
AGS:	Committee on Hazardous Substances (Ausschuss für Gefahrstoffe)
AOX:	adsorbable organically bound halogens
AwSV:	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances that are hazardous to water)
DFG:	German Research Foundation (Deutsche Forschungsgemeinschaft)
DNEL:	Derived No-Effect Level
ICAO/IATA:	International Civil Aviation Organisation/International Air Transport Association-Dangerous Goods Regulations
IMDG-Code:	International Maritime Dangerous Goods-Code
IUCLID:	International Uniform Chemical Information Database
LGK:	Lagerklasse (storage class)
MDI:	Methylenediphenyl diisocyanate
OECD:	Organisation for Economic Co-operation and Development
PBT:	persistent, bioaccumulative and toxic
PNEC:	Predicted No-Effect Concentration
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer
RTECS:	Registry of Toxic Effects of Chemical Substances
TRGS:	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
vPvB:	very persistent and very bioaccumulative

**Literature references and sources for data**

- <http://www.baua.de>
- <http://www.arbeitssicherheit.de>
- <http://www.umweltbundesamt.de>
- <http://www.wingis-online.de>
- <http://www.baua.de/emkg>

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

---

Trade name:	AQUAPANEL® Slot Adhesive (PU)	Product number:	KAQ_0435
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.07.2019

---

**Method used for the classification of the mixture**

The classification was undertaken in accordance with the classification criteria of Annex I of Regulation (EC) No 1272/2008.

**Changes which have been made to the previous version of the safety data sheet**

Revised sections: 1.2, 7.2, 8.1, 8.2, 9.1, 10.4, 11.1, 12.1

**The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.**

Compiled by: **Dr. Michael Urban**  
**Fachberatung Gefahrstoff Gefahrgut**  
Vogelbeerweg 3 D-26180 Rastede-Ipwege / Germany  
Tel.: +49-4402-695620 Fax: +49-4402-695621