



AQUAPANEL® Reinforcing Mesh

Reinforcing mesh with alkali-resistant coating





Description

AQUAPANEL[®] Reinforcing Mesh is an alkali-resistant glass fabric. It is used to reinforce AQUAPANEL[®] Exterior Basecoat/AQUAPANEL[®] Exterior Basecoat – white and AQUAPANEL[®] Joint Filler & Skim Coating – white.

Technical data

Weight/unit area	approx. 160 g/m ²
Mesh size	4 x 4 mm
Initial tear strength	approx. 2200 N/5 cm
Thickness	approx. 0.5 mm
Width	100 cm
Length	50 m
Colour	blue

Working time

Wall area approx. 3-4 minutes/m² Ceiling area approx. 4-5 minutes/m²

Method of delivery/storage

100 cm wide rolls x 50 m long 30 Rolls / Pallet

Store in a dry place and protect from moisture.

Item code: 102584

Processing/application

In exterior walls apply AQUAPANEL[®] Exterior Basecoat 5-7 mm thick or AQUAPANEL[®] Exterior Basecoat – white 4-5 mm thick and spread to achieve a flat surface free from irregularities. Place reinforcing strips of AQUAPANEL[®] Reinforcing Mesh approx. 30 x 50 cm diagonally from the corners of all building openings. The strips must start directly from the corners beneath the full surface fabric layer. Then embed the AQUAPANEL[®] Reinforcing Mesh over the full surface, keeping it free of folds, close to the surface and with 10 cm joint overlaps.

For exterior render layers < 1 mm thick or for felted surfaces or those to be painted, a 20 cm wide additional reinforcing strip of AQUAPANEL[®] Exterior Reinforcing Tape is required over the board joints. The AQUAPANEL[®] Tape (10 cm) can then be omitted.

For exterior and interior ceiling applications and interior wall applications apply AQUAPANEL[®] Joint Filler and Skim Coating – white at least 3-5 mm thick, spread to achieve a flat surface free from irregularities. Then embed the AQUAPANEL[®] Reinforcing Mesh over the full surface, keeping it free of folds, close to the surface and with 10 cm joint overlaps.

Coverage

Approx. 1.10-1.15 m² per m² plastered surface

AQUAPANEL®	AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.
www.AQUAPANEL.com	AQUAPANEL® is a registered trademark.
@ aquapanel.info@knauf.com	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany
© 2017 EN-08/17	All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 5653 Iserlohn, Germany.