

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Revision date: 14.07.2018  
Replacement of version 0015 of 21.07.2017

Version: 0016

# *Knauf Aquapanel GmbH & Co. KG*

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 *Product identifier*

Trade name      **AQUAPANEL® Indoor Joint Adhesive**  
Product number    **KAQ\_0451**  
Item code          **103389**

### 1.2 *Relevant identified uses of the substance or mixture and uses advised against*

Appropriate use:  
The product is used as an adhesive.

#### **Recommended restrictions on use:**

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.

### 1.3 *Details of the supplier of the safety data sheet*

Knauf Aquapanel GmbH & Co. KG  
Zur Helle 11  
D-58638 Iserlohn

Telephone: +49-2374-50360

Fax: +49-2374-5036300

e-mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)

e-mail-address of the competent person responsible for this Safety Data Sheet:

[urban-finking.gefstoff@t-online.de](mailto:urban-finking.gefstoff@t-online.de)

#### **Technical contact:**

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn

Telephone: +49-2374-50360

Fax: +49-2374-5036300

### 1.4 *Emergency telephone number*

Giftnotruf Berlin, Advice in German and English

Telephone: +49-30-30686 790

(24 hours, Monday – Sunday)

## SECTION 2: Hazards identification

### 2.1 *Classification of the substance or mixture*

The mixture does not meet the criteria for a classification as hazardous in accordance with the current version of Regulation (EC) No 1272/2008.

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

**2.2 Label elements**

Hazard pictogram(s):	No pictogram
Signal word(s):	No signal word
Product identifier:	AQUAPANEL® Indoor Joint Adhesive
Hazard statements:	Not required
Precautionary statements: P102	Keep out of reach of children.
Supplemental hazard information:	
EUH208	Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Special labelling in accordance with Article 58 (3) of Regulation (EU) No 528/2012: Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1) as biocidal active substance.

**Remark:**

- The use of the EUH208 sentence is based on the CEPE Guidance on labelling decorative paint with skin sensitizing biocides<sup>5</sup>.
- The statement EUH210 must only appear on the label on the packaging of mixtures not intended for the general public.
- The precautionary statement P102 must only appear on the label of packaging supplied to the general public.

**2.3 Other hazards**

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.  
The product is classified as highly hazardous to water.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

REACH registration number:  
The ingredients do not require registration according to Regulation (EC) No 1207/2006 [REACH] or the registration is scheduled at a later date.

**Characterisation**

This product is a mixture. It is an aqueous polymer dispersion.

**Substances presenting a health/environmental hazard within the meaning of Regulation (EC) No 1272/2008**

CAS No	EC No	Identification	% by weight	Classification
55965-84-9	not available	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1)	≥ 0.00015 – < 0.0015	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1B; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 Acute Tox. 3; H331 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

See subsection 2.2 for further details. Full text of the hazard statements see Section 16.

**Substances for which Union workplace exposure limits have been assigned (see also Section 8.)**

No substances.

**Additional information**

None.

---

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

---

## SECTION 4: First aid measures

### 4.1 *Description of first aid measures*

#### **General information**

Take off contaminated clothing immediately and wash before reuse.  
Emergency eyewash should be provided in the immediate working surroundings.

#### **In case of inhalation**

If vapours or decomposition products are inhaled, remove the affected person to fresh air.

#### **In case of contact with skin**

In case of contact with skin wash off immediately with soap and plenty of water.  
Do not wash with solvents or diluting agent.  
By continuous complaints seek medical advice.

#### **In case of contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do.

#### **In case of ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting.  
Take medical treatment immediately.

### 4.2 *Most important symptoms and effects, both acute and delayed*

Possible allergic reaction in case of skin contact.

### 4.3 *Indication of any immediate medical attention and special treatment needed*

Treat symptomatically. No information available.

## SECTION 5: Firefighting measures

### 5.1 *Extinguishing media*

#### **Suitable extinguishing media**

Water spray jet, foam, carbon dioxide, dry powder.

#### **Unsuitable extinguishing media**

Full water jet.

### 5.2 *Special hazards arising from the substance or mixture*

In the event of fire the following can be released: carbon dioxide, carbon monoxide.

### 5.3 *Advice for firefighters*

Wear self-contained breathing apparatus.  
Do not inhale explosion and/or combustion gases.  
Cool endangered containers with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

## SECTION 6: Accidental release measures

### 6.1 *Personal precautions, protective equipment and emergency procedures*

#### **For non-emergency personnel**

Ensure adequate ventilation. Use personal protective clothing.  
Keep away from unprotected people.

#### **For emergency responders**

For suitable fabric for personal protective clothing see Section 8.

### 6.2 *Environmental precautions*

Do not discharge into the drains, the aquatic environment and soil.  
In case of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3 *Methods and material for containment and cleaning up*

Absorb with liquid-binding material (e.g. sand, kieselguhr, silica gel, acid binder, universal binder, sawdust).  
Send in suitable containers for recovery or disposal.

### 6.4 *Reference to other sections*

For personal protective equipment see also Section 8. For disposal considerations see also Section 13.

## SECTION 7: Handling and storage

### 7.1 *Precautions for safe handling*

#### **Advice on safe handling**

Ensure adequate ventilation.  
Comply with the minimum standards in accordance with TRGS 500<sup>1</sup>.  
Moreover, comply with the protective measures in accordance with TRGS 401<sup>1</sup>.  
In designing the work process the model solutions of the Control Guidance Sheet 120<sup>1</sup> must be taken into consideration in case of small-area skin contact (e.g. splashes) regardless on the duration of skin contact.  
In designing the work process the model solutions of the Control Guidance Sheet 120<sup>1</sup> must be taken into consideration in case of large-area skin contact (wetting of the skin) and short-term effect (duration of skin contact less than 15 minutes per shift).  
In designing the work process the model solutions of the Control Guidance Sheets 120<sup>1</sup> and 250<sup>1</sup> must be taken into consideration in case of large-area skin contact (wetting of the skin) and long-term effect (duration of skin contact more than 15 minutes per shift).

#### **Advice on general occupational hygiene**

Avoid contact with eyes and skin. Take off contaminated clothing immediately and wash before reuse.  
At work do not eat, drink, smoke or take drugs.  
After worktime and before breaks the affected skin areas must be thoroughly cleaned.  
After work protect skin by using skin protective cream. Set out skin protection guidelines.  
Emergency eyewash should be provided in the immediate working surroundings.

### 7.2 *Conditions for safe storage, including any incompatibilities*

#### **Advice on protection against fire and explosion**

No special measures necessary.

#### **Requirements for storage rooms and vessels**

Keep container tightly closed. Do not use coated metal containers.

#### **Advice on storage compatibility**

Do not store together with strong oxidising agents, strong acids and strong alkalies.  
The information about joint storage given in Table 2 of TRGS 510<sup>1</sup> must be observed.

#### **Further information on storage conditions**

Keep only in the original container in a cool, well ventilated place. Protect from frost.  
Recommended storage temperature: 15 – 25°C.  
Storage period: 12 months.

#### **Storage class (for Germany only)**

LGK 12 (non-combustible liquids) in accordance with TRGS 510<sup>1</sup>.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

### 7.3 *Specific end use(s)*

The product is only intended for the uses mentioned under subsection 1.2.  
In accordance with GISBAU (Information system of the the German professional associations for building and construction industry):  
GISCODE<sup>4</sup>: D 1 (solvent free, dispersion laminate adhesives)

## SECTION 8: Exposure controls/personal protection

### 8.1 *Control parameters*

The product does not contain substances above cut-off values for which exposure limit values have been assigned.

### 8.2 *Exposure controls*

#### **Appropriate engineering controls**

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.  
See also subsection 7.1.

#### **Individual protection measures, such as personal protective equipment**

Personal protective equipment needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer/supplier of the personal protective equipment.

#### **Eye/face protection**



Tightly fitting safety glasses in accordance with EN 166.

#### **Hand protection**



In case of operations where skin contact is possible, wear suitable protective gloves.  
Chemical protective gloves needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. Information on appropriate protective gloves is currently not available.  
In cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.  
The protective gloves to be used must comply with the specifications of the standard EN 374.

#### **Body protection**

Closed work clothing.

#### **Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.

#### **Thermal hazards**

Not relevant.

#### **Environmental exposure controls**

See Section 6.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	liquid
Colour:	white
Odour:	characteristic
Odour threshold:	no data available
pH (as supplied) (20°C):	4.5
pH (of an aqueous solution) (20°C):	not determined
Melting point/freezing point (°C):	not determined
Boiling point and boiling range (°C):	100
Flash point (°C), closed cup:	not relevant
Evaporation rate:	not determined
Flammability (solid, gas):	not relevant
Upper flammability or explosive limit:	not relevant
Lower flammability or explosive limit:	not relevant
Vapour pressure (20°C) (hPa):	not determined
Vapour density (20°C):	not determined
Relative density:	approx. 1.1
Solubility in water:	miscible
Soluble in:	not determined
Partition coefficient: n-octanol/water:	no data available
Auto-ignition temperature (°C):	not relevant
Decomposition temperature (°C):	not determined
Dynamic viscosity (mPa · s):	approx. 120000
Explosive properties:	not explosive
Oxidising properties:	not relevant

### 9.2 Other information

None.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available for the product.

### 10.2 Chemical stability

The product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

Reaction with strong oxidising agents, strong acids and strong alkalies possible.

### 10.4 Conditions to avoid

Protect from frost.

### 10.5 Incompatible materials

Reaction with oxidising agents, strong acids and strong alkalies possible.  
Do not use coated metal containers.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.  
For hazardous combustion products see subsection 5.2.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

## SECTION 11: Toxicological information

### 11.1 *Information on toxicological effects*

No data are available for the product.

#### **Acute toxicity**

LD50 rat, oral	(mg/kg)	No data available.
LD50 rat, dermal	(mg/kg)	No data available.
LC50 rat, inhalation	(mg/l/4h)	No data available.

#### **Skin corrosion/irritation**

No data are available.

#### **Serious eye damage/irritation**

Irritant effect on eyes No data available.

#### **Respiratory or skin sensitisation**

The product has not been tested.

The product contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1). This substance is classified as sensitising.

#### **Germ cell mutagenicity**

The mixture does not contain substances classified as germ cell mutagens.

#### **Carcinogenicity**

The mixture does not contain substances classified as carcinogenic.

#### **Reproductive toxicity**

The mixture does not contain substances classified as toxic for the reproduction.

#### **Specific target organ toxicity (STOT)-single exposure**

The mixture does not contain substances classified as being a specific target organ toxicant after single exposure.

#### **Specific target organ toxicity (STOT)-repeated exposure**

The mixture does not contain substances classified as being a specific target organ toxicant after repeated exposure.

#### **Aspiration hazard**

The mixture does not contain aspiration toxicants.

#### **Symptoms related to the physical, chemical and toxicological characteristics**

The product has not been tested.

Possible allergic reaction in case of skin contact.

#### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

The product has not been tested.

Persons suffering from an allergy may be sensitive to very low concentrations of allergenic substances and should consequently have no further contact with this product (possibility of an allergic reaction).

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

LC50 (fish)	No data available.
EC50 (daphnia)	No data available.
IC50 (algae)	No data available.

#### Behaviour in sewage works:

The behaviour of the product in sewage treatment plants has not been tested.  
Treat by state-of-the-art technology before discharging into drains.

### 12.2 Persistence and degradability

The product has not been tested.	
Chemical oxygen demand (COD)	Not relevant.
Biochemical oxygen demand (BOD5)	Not relevant.
AOX-hint	Not to apply.

### 12.3 Bioaccumulative potential

The product has not been tested.

### 12.4 Mobility in soil

The product has not been tested.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Other adverse effects

Ozone depletion potential	No data available.
Photochemical ozone creation potential	No data available.
Global warming potential	No data available.

The product is classified as highly hazardous to water.

#### Contains according to the formulation following compounds of directives 2006/11/EC and 80/68/EEC:

List II: biocides and their derivatives not appearing in List I.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste disposal according to official state regulations.  
Consult the local waste disposal expert about waste disposal.  
Sewage disposal must be avoided.

#### Disposal operations/recovery operations according to Directive 2008/98/EC

Disposal operations:	D 10	Incineration on land
Recovery operations:	R 3	Recycling/reclamation of organic substances which are not used as solvents

#### Properties of waste which render it hazardous in accordance with Annex III of Directive 2008/98/EC

Not relevant.

#### Product/unused product

Waste disposal corresponding to European Waste Catalogue. Wastes must be classified with respect to their origin and depending on different processing steps. The waste codes mentioned as follows are only constituted as our recommendations. Referring to the particular case they should be completed or revised.

EC waste code:	08 04 10
Waste notation:	Waste adhesives and sealants other than those mentioned in 08 04 09

#### Contaminated packaging

Recommendation: Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Recommended cleansing agent: Water.

Packaging that cannot be cleaned:

EC waste code:	15 01 05
Waste notation:	Composite packaging



**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

**SECTION 14: Transport information**

- 14.1 UN number**  
No dangerous good in accordance with the UN Model Regulations (ADR/RID/ADN/IMDG/ICAO/IATA).
- 14.2 UN proper shipping name**  
Not relevant.
- 14.3 Transport hazard class(es)**  
Not relevant.
- 14.4 Packing group**  
Not relevant.
- 14.5 Environmental hazards**  
Not relevant.
- 14.6 Special precautions for user**  
Not relevant.
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**  
Not relevant.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Information regarding relevant Union safety, health and environmental provisions**

None.

**Information regarding national laws/national measures that may be relevant (for Germany only)**

Indications on restriction of occupation:	Not relevant
Major Accident Ordinance:	Not relevant
Fire and explosion hazards:	Not relevant
Regulation on clean air (TA Luft):	Not relevant
Water hazard class:	WGK 3 – highly hazardous to water (deduction of the WGK according to Annex 1 No 5.2 AwSV) <sup>3</sup> The German Ordinance on facilities for handling substances that are hazardous to water (AwSV) has to be observed.
German Ordinance on Hazardous Substances (in accordance with EC-Directive 98/24/EC):	Articles 6, 7, 8 and 14 must be observed.
Technical Rules for Hazardous Substances <sup>1</sup> :	TRGS 400, 401, 500, 510, 555
Rules of the employers' liability insurance association <sup>2</sup> :	DGUV Regel 112-192, 112-195
Classification in accordance with the easy-to-use workplace control scheme for hazardous substances of the Federal Institute for Occupational Safety and Health, version 2.2, 2014 <sup>6</sup> : skin contact:	hazard group HA

**15.2 Chemical safety assessment**

No chemical safety assessment has been carried out for a substance in the product.

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	14.07.2018

**SECTION 16: Other information**

**Keeping (restrictions)** Article 8 paragraphs 5 and 6 of the German Ordinance on Hazardous Substances has to be observed. (only for Germany)

**Supply** to industry consumer

**Full text of the hazard statements referred to under subsections 2.1 and 3.2 of the Safety Data Sheet**

H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Key to abbreviations and acronyms used in the safety data sheet**

ADN:	Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ADR:	Accord européen relatif au transport international des marchandises dangereuses par route
AOX:	adsorbable organically bound halogens
AwSV:	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances that are hazardous to water)
CEPE:	Conseil Européen de l'Industrie des Peintures, des Encres d'Imprimerie et des Couleurs d'Arts (European Council of Paint, Printing Ink and Artist's Colours Industry)
ICAO/IATA:	International Civil Aviation Organisation/International Air Transport Association-Dangerous Goods Regulations
IMDG-Code:	International Maritime Dangerous Goods-Code
LGK:	Lagerklasse (storage class)
PBT:	persistent, bioaccumulative and toxic
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer
TRGS:	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
VCI:	Verband der chemischen Industrie (German Association of Chemical Industry)
vPvB:	very persistent and very bioaccumulative

**Literature references and sources for data**

- <http://www.baua.de>
- <http://www.arbeitssicherheit.de>
- <http://www.umweltbundesamt.de>
- <http://www.wingis-online.de>
- <http://www.cepe.org/efede/public.htm#!HTML/3008>
- <http://www.baua.de/emkg>

**Method used for the classification of the mixture**

The product does not meet the criteria for a classification as hazardous in accordance with the current version of Regulation (EC) No 1272/2008.

**Changes which have been made to the previous version of the safety data sheet**

Revised sections: 2.3, 15.1, 16

**The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.**

Compiled by: **Dr. Michael Urban**  
**Fachberatung Gefahrstoff Gefahrgut**  
Vogelbeerweg 3 D-26180 Rastede-Ipwege / Germany  
Tel.: +49-4402-695620 Fax: +49-4402-695621