

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Revision date: 24.05.2023
Replacement of version 0021 of 20.06.2022

Version: 0022

Knauf Aquapanel GmbH & Co. KG

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 *Product identifier*

Trade name **AQUAPANEL® Indoor Joint Adhesive**
Product number **KAQ_0451**
Item code **103389**

1.2 *Relevant identified uses of the substance or mixture and uses advised against*

Appropriate use:
The product is used as an adhesive.

Recommended restrictions on use:

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.

1.3 *Details of the supplier of the safety data sheet*

Knauf Aquapanel GmbH & Co. KG
Zur Helle 11
D-58638 Iserlohn

Telephone: +49-2374-50360
e-mail: aquapanel.info@knauf.com

Fax: +49-2374-5036300

e-mail-address of the competent person responsible for this Safety Data Sheet:
info@gefstoff.de

Technical contact:

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn
Telephone: +49-2374-50360 Fax: +49-2374-5036300

1.4 *Emergency telephone number*

Giftnotruf der Charité - Universitätsmedizin Berlin, Campus Benjamin Franklin, Haus VIII (Wirtschaftsgebäude), UG
Hindenburgdamm 30, 12203 Berlin
Giftnotruf Berlin +49-30-30686 700 (Advice in German and English)
(24 hours, Monday – Sunday)

SECTION 2: Hazards identification

2.1 *Classification of the substance or mixture*

The product contains sensitising substances in concentrations above one tenth of the specific concentration limit which leads to a classification of the mixture as skin sensitising.
The special labelling requirements of section 2.8 of Annex II of the Regulation must be applied.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

2.2 Label elements

Hazard pictogram(s):	No pictogram
Signal word(s):	No signal word
Product identifier:	AQUAPANEL® Indoor Joint Adhesive
Hazard statements:	Not required
Precautionary statements: P102	Keep out of reach of children.
Supplemental hazard information:	
EUH208	Contains reaction mass of 5-chloro-2-methyl-2 <i>H</i> -isothiazol-3-one and 2-methyl-2 <i>H</i> -isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Special labelling in accordance with Article 58 (3) of Regulation (EU) No 528/2012:	Contains reaction mass of 5-chloro-2-methyl-2 <i>H</i> -isothiazol-3-one and 2-methyl-2 <i>H</i> -isothiazol-3-one (3:1) as biocidal active substance.

Remark:

- The statement EUH210 must only appear on the label on the packaging of mixtures not intended for the general public.
- The precautionary statement P102 must only appear on the label of packaging supplied to the general public.

2.3 Other hazards

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.
The product is classified as highly hazardous to water.

SECTION 3: Composition/information on ingredients
3.2 Mixtures

REACH registration number:
The ingredients do not require registration according to Regulation (EC) No 1207/2006 [REACH] (exempted from registration or the annual tonnage does not require a registration).

Characterisation

This product is a mixture. It is an aqueous polymer dispersion.

Substances presenting a health/environmental hazard within the meaning of Regulation (EC) No 1272/2008

CAS No	EC No	Identification	% by weight	Classification
55965-84-9	not available	reaction mass of 5-chloro-2-methyl-2 <i>H</i> -isothiazol-3-one and 2-methyl-2 <i>H</i> -isothiazol-3-one (3:1)	≥ 0.00015 – < 0.0015	Acute Tox. 3; H301 Acute Tox. 2; H310 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-factor: M = 100 M-factor (chronic): M = 100

See subsection 2.2 for further details. Full text of the hazard statements see Section 16.

Substances for which there are Union workplace exposure limits (see also Section 8.)

None.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

(continued from 3.2 Mixtures)

Additional information

Specific concentration limits for reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) in accordance with Annex VI of Regulation (EC) No 1272/2008:

Eye Dam. 1; H318:	C ≥ 0.6%
Eye Irrit. 2; H319:	C ≥ 0.06 - < 0.6%
Skin Corr. 1C; H314:	C ≥ 0.6%
Skin Irrit. 2; H315:	C ≥ 0.06 - < 0.6%
Skin Sens. 1A; H317:	C ≥ 0.0015%

The product contains 2-3% 2-(2-butoxyethoxy)ethyl acetate (CAS No: 124-17-4; EC No: 204-685-9).
National occupational exposure limit values for various EU member states have been assigned (see subsection 8.1).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing immediately and wash before reuse.
Emergency eyewash should be provided in the immediate working surroundings.

In case of inhalation

If vapours or decomposition products are inhaled, remove the affected person to fresh air.

In case of contact with skin

In case of contact with skin wash off immediately with soap and plenty of water.
Do not wash with solvents or diluting agent. By continuous complaints seek medical advice.

In case of contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do.

In case of ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting.
Take medical treatment immediately.

4.2 Most important symptoms and effects, both acute and delayed

Possible allergic reaction in case of skin contact.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet, foam, carbon dioxide, dry powder.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released: carbon dioxide, carbon monoxide.

5.3 Advice for firefighters

Wear self-contained breathing apparatus. Do not inhale explosion and/or combustion gases.
Cool endangered containers with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

SECTION 6: Accidental release measures

6.1 *Personal precautions, protective equipment and emergency procedures*

For non-emergency personnel

Ensure adequate ventilation. Use personal protective clothing. Keep away from unprotected people.

For emergency responders

For suitable fabric for personal protective clothing see Section 8.

6.2 *Environmental precautions*

Do not discharge into the drains, the aquatic environment and soil.

6.3 *Methods and material for containment and cleaning up*

Absorb with liquid-binding material (e.g. sand, kieselguhr, silica gel, acid binder, universal binder, sawdust).

Send in suitable containers for recovery or disposal.

6.4 *Reference to other sections*

For personal protective equipment see also Section 8. For disposal considerations see also Section 13.

SECTION 7: Handling and storage

7.1 *Precautions for safe handling*

Advice on safe handling

Ensure adequate ventilation. Comply with the minimum standards in accordance with TRGS 500¹.

Moreover, comply with the protective measures in accordance with TRGS 401¹.

In designing the work process the model solutions of the Control Guidance Sheet 120¹ must be taken into consideration in case of small-area skin contact (e.g. splashes) regardless on the duration of skin contact.

In designing the work process the model solutions of the Control Guidance Sheet 120¹ must be taken into consideration in case of large-area skin contact (wetting of the skin) and short-term effect (duration of skin contact less than 15 minutes per shift).

In designing the work process the model solutions of the Control Guidance Sheets 120¹ and 250¹ must be taken into consideration in case of large-area skin contact (wetting of the skin) and long-term effect (duration of skin contact more than 15 minutes per shift).

Advice on general occupational hygiene

Avoid contact with eyes and skin. Take off contaminated clothing immediately and wash before reuse.

At work do not eat, drink, smoke or take drugs.

After worktime and before breaks the affected skin areas must be thoroughly cleaned.

After work protect skin by using skin protective cream. Set out skin protection guidelines.

Emergency eyewash should be provided in the immediate working surroundings.

7.2 *Conditions for safe storage, including any incompatibilities*

Advice on protection against fire and explosion

No special measures necessary.

Requirements for storage rooms and vessels

Keep container tightly closed. Do not use coated metal containers.

Advice on storage compatibility

Do not store together with strong oxidising agents, strong acids and strong alkalis.

The information about joint storage given in Table 12 of TRGS 510¹ must be observed.

Further information on storage conditions

Keep only in the original container in a cool, well ventilated place. Protect from frost.

Recommended storage temperature: 15 – 25°C. Storage period: 18 months.

Storage class (for Germany only)

LGK 12 in accordance with TRGS 510¹.

7.3 *Specific end use(s)*

The product is only intended for the uses mentioned under subsection 1.2.

In accordance with GISBAU (Information system of the the German professional associations for building and construction industry):

GISCODE⁴: D 1 (solvent free, dispersion laminate adhesives)

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	Revision date:	24.05.2023
Telephone:	+49-(0)2374-50360		

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

CAS number	Identification	Limit values	Remarks
124-17-4	2-(2-butoxyethoxy)ethyl acetate	10 ppm – 67 mg/m ² inhalable aerosol and vapour 15 ppm – 130 mg/m ³ 10 ppm – 85 mg/m ³ 15 ppm – 100 mg/m ² inhalable aerosol and vapour 30 ppm – 250 mg/m ³ 15 ppm – 127.5 mg/m ³	National limit values – eight hours Germany Sweden Switzerland National limit values – short term Germany Sweden Switzerland
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	0.05 mg/m ³ 2 mg/m ³ 0.2 mg/m ³ inhalable fraction* 0.2 mg/m ³ inhalable fraction 0.4 mg/m ³ inhalable fraction* 0.4 mg/m ³ inhalable fraction	National limit values – eight hours Austria Denmark Germany Switzerland National limit values – short term Germany Switzerland

* Germany: This data is recommended by scientific experience and is not established law.

DNEL values

Additional limit values for 2-(2-butoxyethoxy)ethyl acetate in accordance with the registration dossier:

general population, long-term exposition: oral, systemic effect: 7.9 mg/kg_{bw}/d

Additional limit values for reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) in accordance with the registration dossier:

worker, long-term exposition: inhalation, local effect: 0.02 mg/m³
worker, short-term exposition: inhalation, local effect: 0.04 mg/m³
general population, long-term exposition: inhalation, systemic effect: 0.02 mg/m³
general population, short-term exposition: inhalation, local effect: 0.04 mg/m³
general population, long-term exposition: oral, systemic effect: 0.09 mg/kg_{bw}/d
general population, short-term exposition: oral, systemic effect: 0.11 mg/kg_{bw}/d

PNEC values

Additional limit values for 2-(2-butoxyethoxy)ethyl acetate in accordance with the registration dossier:

aquatic, fresh water: 0.108 mg/l
aquatic, fresh water, intermittent release: 0.6 mg/l
aquatic, marine water: 0.011 mg/l
aquatic, sewage treatment plant: 100 mg/l
sediment, fresh water: 0.8 mg/kg_{dw}
sediment, marine water: 0.08 mg/kg_{dw}
soil environment: 0.29 mg/kg_{dw}
secondary intoxication, food, oral: 70 mg/kg food

Additional limit values for reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) in accordance with the registration dossier:

aquatic, fresh water: 3.39 µg/l
aquatic, fresh water, intermittent release: 3.39 µg/l
aquatic, marine water: 3.39 µg/l
aquatic, marine water, intermittent release: 3.39 µg/l
aquatic, sewage treatment plant: 0.23 mg/l
sediment, fresh water: 0.027 mg/kg_{dw}
sediment, marine water: 0.027 mg/kg_{dw}
soil environment: 0.01 mg/kg_{dw}

The methods for measuring chemical agents in workplace atmosphere must meet the general requirements of EN 481, EN 482 and EN 689.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

8.2 Exposure controls

Appropriate engineering controls

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See also subsection 7.1.

Individual protection measures, such as personal protective equipment

Personal protective equipment needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer/ supplier of the personal protective equipment.

Eye/face protection



Tightly fitting safety glasses in accordance with EN 166.

Hand protection



In case of operations where skin contact is possible, wear suitable protective gloves.
Chemical protective gloves needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled.
Suitable: protective gloves of fluoro rubber (Viton); > 0.4 mm.
Wear cotton undermitten if possible.
The protective gloves to be used must comply with the specifications of the standard EN 374.

Body protection

Closed work clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Thermal hazards

Not relevant.

Environmental exposure controls

See Section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	liquid
Colour:	white
Odour:	characteristic
Odour threshold:	no data available
Melting point/freezing point (°C):	not determined
Boiling point/initial boiling point/boiling range (°C):	100
Flammability:	not flammable
Lower explosion limit:	not applicable
Upper explosion limit:	not applicable
Flash point (°C), closed cup:	not applicable
Auto-ignition temperature (°C):	not applicable
Decomposition temperature (°C):	not determined
pH (as supplied) (20°C):	approx. 5
Kinematic viscosity (mm ² /s):	18182
Solubility in water:	miscible
Soluble in:	not determined
Partition coefficient: n-octanol/water (log value):	no data available
Vapour pressure (20°C) (hPa):	no data available
Relative density:	approx. 1.1
Relative vapour density (20°C):	not determined
Particle characteristics:	not applicable

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

9.2 Other information
 None.

SECTION 10: Stability and reactivity
10.1 Reactivity

No data available for the product.

10.2 Chemical stability

The product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Reaction with strong oxidising agents, strong acids and strong alkalies possible.

10.4 Conditions to avoid

Protect from frost.

10.5 Incompatible materials

 Reaction with oxidising agents, strong acids and strong alkalies possible.
 Do not use coated metal containers.

10.6 Hazardous decomposition products

 No hazardous decomposition products known.
 For hazardous combustion products see subsection 5.2.

SECTION 11: Toxicological information
11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product has not been tested.

Acute toxicity

LD50 rat, oral	(mg/kg)	6500 66	(2-(2-butoxyethoxy)ethyl acetate) (RTECS) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 401)
LC50 rat, inhalation	(mg/l/4h)	7.25 0.171	(2-(2-butoxyethoxy)ethyl acetate) (RTECS) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 403)
LD50 rabbit, dermal	(mg/kg)	5390 660	(2-(2-butoxyethoxy)ethyl acetate) (OECD Test Guideline 402) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (registration dossier)

Skin corrosion/irritation

Irritant effect on skin (rabbit)	Not irritating	(2-(2-butoxyethoxy)ethyl acetate) (OECD Test Guideline 404)
	Corrosive	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 404)

Serious eye damage/irritation

Irritant effect on eyes (rabbit)	Not irritating	(2-(2-butoxyethoxy)ethyl acetate) (registration dossier)
	Corrosive	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 405)

Respiratory or skin sensitisation

 The product has not been tested.
 The product contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). This substance is classified as sensitising by skin contact.

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451	
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		Revision date:	24.05.2023
Telephone:	+49-(0)2374-50360			

(continued from 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008)

Germ cell mutagenicity

The mixture does not contain substances classified as germ cell mutagens.

Carcinogenicity

The mixture does not contain substances classified as carcinogenic.

Reproductive toxicity

The mixture does not contain substances classified as toxic for the reproduction.

Specific target organ toxicity (STOT)-single exposure

The mixture does not contain substances classified as being a specific target organ toxicant after single exposure.

Specific target organ toxicity (STOT)-repeated exposure

The mixture does not contain substances classified as being a specific target organ toxicant after repeated exposure.

Aspiration hazard

The mixture does not contain aspiration toxicants.

Symptoms related to the physical, chemical and toxicological characteristics

The product has not been tested.

Possible allergic reaction in case of skin contact.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

The product has not been tested.

Persons suffering from an allergy may be sensitive to very low concentrations of allergenic substances and should consequently have no further contact with this product (possibility of an allergic reaction).

11.2 Information on other hazards

The mixture has not been tested.

Endocrine disrupting properties

No data available for the mixture.

Other information

None.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity:

96 h LC50	(fish)	> 50 - < 70 mg/l	(Danio rerio; zebrafish) (2-(2-butoxyethoxy)ethyl acetate) (OECD Test Guideline 203)
		0.19 mg/l	(Oncorhynchus mykiss; rainbow trout) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (EPA OPP 72-1)
35 d NOEC	(fish)	≥ 46.4 µg/l	(Danio rerio; zebrafish) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 210)
48 h LC50	(daphnia)	664 mg/l	(Daphnia magna) (2-(2-butoxyethoxy)ethyl acetate) (registration dossier)
48 h EC50	(daphnia)	0.16 mg/l	(Daphnia magna) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (EPA OPP 72-2)
21 d NOEC	(daphnia)	0.004 mg/l	(Daphnia magna) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (EPA OPP 72-4)
72 h EC50	(algae)	520 mg/l	(Raphidocelis subcapitata) (2-(2-butoxyethoxy)ethyl acetate) (registration dossier)
		6.3 µg/l	(Skeletonema costatum) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 201)

Behaviour in sewage works:

The behaviour of the product in sewage treatment plants has not been tested.

Treat by state-of-the-art technology before discharging into drains.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

12.2 Persistence and degradability

The product has not been tested.

- 2-(2-butoxyethoxy)ethyl acetate: 102.3%/20d (OECD Test Guideline 301B). Readily biodegradable.
- Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1): 55.8%/28d (OECD Test Guideline 301B). Not readily biodegradable.

Chemical oxygen demand (COD) Not relevant.
 Biochemical oxygen demand (BOD5) Not relevant.
 AOX-hint Not to apply.

12.3 Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water:

1.7	(23°C; pH 6.4)	(2-(2-butoxyethoxy)ethyl acetate)	(OECD Test Guideline 117)
0.326	(24°C)	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1))	(OECD Test Guideline 107)

12.4 Mobility in soil

The product has not been tested.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available for the mixture.

12.7 Other adverse effects

Ozone depletion potential No data available.
 Photochemical ozone creation potential No data available.
 Global warming potential No data available.

The product is classified as highly hazardous to water.

Contains according to the formulation following compounds of directives 2006/11/EC and 80/68/EEC:

List II: biocides and their derivatives not appearing in List I.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste disposal according to official state regulations.
 Sewage disposal must be avoided.
 Consult the local waste disposal expert about waste disposal.

Disposal operations/recovery operations according to Directive 2008/98/EC

Disposal operations:	D 10	Incineration on land
Recovery operations:	R 3	Recycling/reclamation of organic substances which are not used as solvents

Properties of waste which render it hazardous in accordance with Annex III of Directive 2008/98/EC

Not relevant.

Product/unused product

Waste disposal corresponding to European Waste Catalogue. Wastes must be classified with respect to their origin and depending on different processing steps. The waste codes mentioned as follows are only constituted as our recommendations. Referring to the particular case they should be completed or revised.

EC waste code: 08 04 10
 Waste notation: Waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

Recommendation: Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Recommended cleansing agent: Water.

Packaging that cannot be cleaned:

EC waste code: 15 01 05
 Waste notation: Composite packaging

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

SECTION 14: Transport information

- 14.1 UN number or ID number**
No dangerous good in accordance with the UN Model Regulations (ADR/RID/ADN/IMDG/ICAO/IATA).
- 14.2 UN proper shipping name**
Not relevant.
- 14.3 Transport hazard class(es)**
Not relevant.
- 14.4 Packing group**
Not relevant.
- 14.5 Environmental hazards**
Not relevant.
- 14.6 Special precautions for user**
Not relevant.
- 14.7 Maritime transport in bulk according to IMO instruments**
Not relevant.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Information regarding relevant Union safety, health and environmental provisions

- Conditions of restriction in accordance with Annex XVII Regulation (EC) No 1907/2006: None
- The mixture does not contain substances classified as substances of very high concern (SVHC) in accordance with Article 59 of the Regulation (EC) No 1907/2006 in a concentration of 0.1% or more.

Information regarding national laws/national measures that may be relevant (for Germany only)

Indications on restriction of occupation:	Not relevant
Major Accident Ordinance:	Not relevant
Fire and explosion hazards:	Not relevant
Regulation on clean air (TA Luft):	Not relevant
Water hazard class:	WGK 3 – highly hazardous to water (deduction of the WGK according to Annex 1 No 5.2 AwSV) ³ The German Ordinance on facilities for handling substances that are hazardous to water (AwSV) has to be observed.
German Ordinance on Hazardous Substances (in accordance with EC-Directive 98/24/EC):	Articles 6, 7, 8 and 14 must be observed.
Technical Rules for Hazardous Substances ¹ :	TRGS 400, 401, 500, 510, 555, 900
Rules of the employers' liability insurance association ² :	DGUV Regel 112-192, 112-195
Classification in accordance with the easy-to-use workplace control scheme for hazardous substances of the Federal Institute for Occupational Safety and Health, version 2.2, 2014 ⁵ : skin contact:	hazard group HA

- 15.2 Chemical safety assessment**
No chemical safety assessment has been carried out for the mixture.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

SECTION 16: Other information

Keeping (restrictions) Article 8 paragraphs 5 and 6 of the German Ordinance on Hazardous Substances has to be observed. (only for Germany)

Supply to professional user, industrial user, to the general public

Full text of the hazard statements referred to under sections 2 and 3 of the Safety Data Sheet

H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction
EUH210	Safety data sheet available on request.

Key or legend to abbreviations and acronyms used in the safety data sheet

ADN:	Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ADR:	Accord relatif au transport international des marchandises dangereuses par route
AOX:	adsorbable organically bound halogens
AwSV:	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances that are hazardous to water)
CEPE:	Conseil Européen de l'Industrie des Peintures, des Encres d'Imprimerie et des Couleurs d'Arts (European Council of Paint, Printing Ink and Artist's Colours Industry)
DNEL:	Derived No-Effect Level
EPA:	Environmental Protection Agency
ICAO/IATA:	International Civil Aviation Organisation/International Air Transport Association-Dangerous Goods Regulations
IMDG-Code:	International Maritime Dangerous Goods-Code
IMO:	International Maritime Organization
LGK:	Lagerklasse (storage class)
NOEC:	No Observed Effect Concentration
OECD:	Organisation for Economic Co-operation and Development
OPP:	Office of Pesticide Programs
PBT:	persistent, bioaccumulative and toxic
PNEC:	Predicted No-Effect Concentration
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer
RTECS:	Registry of Toxic Effects of Chemical Substances
TRGS:	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
VCI:	Verband der chemischen Industrie (German Association of Chemical Industry)
vPvB:	very persistent and very bioaccumulative

Literature references and sources for data

- <https://www.baua.de>
- <https://www.arbeitssicherheit.de>
- <https://www.umweltbundesamt.de>
- <https://www.wingis-online.de>
- <https://www.baua.de/emkg>

Method used for the classification of the mixture

The assessment of the product was undertaken in accordance with the classification criteria of Annex I of Regulation (EC) No 1272/2008.



Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Indoor Joint Adhesive	Product number:	KAQ_0451
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	24.05.2023

Changes which have been made to the previous version of the safety data sheet

Revised sections: 8.1, 11.1, 12.1

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Compiled by:

Dr. Michael Urban
Fachberatung Gefahrstoff Gefahrgut
Vogelbeerweg 3 D-26180 Rastede-Ipwege / Germany
Tel.: +49-4402-695620 Fax: +49-4402-695621