



AQUAPANEL®

08/2017

AQUAPANEL® Exterior Dispersion Plaster – white

Exterior render - ready-to-use

Description

AQUAPANEL® Exterior Dispersion Plaster – white is a ready-to-use exterior render with a pasty consistency as supplied. It allows diffusion, is water-repellent, and can be worked by hand or using a machine. For application on AQUAPANEL® Exterior Basecoat and AQUAPANEL® Exterior Basecoat – white. The product is flexible and can absorb thermal expansion and contraction without delamination under normal conditions.

The composition of AQUAPANEL® Exterior Dispersion Plaster – white prevents fungal attack on outside walls.

AQUAPANEL® Exterior Dispersion Plaster – white is applied onto dry reinforcing layers of AQUAPANEL® Exterior Basecoat/ AQUAPANEL® Exterior Basecoat – white and AQUAPANEL® Reinforcing Mesh, after the application of AQUAPANEL® Basecoat Primer.

Mixing

Stir the content of the buckets thoroughly. Look for the same batch numbers or mix together enough plaster to cover a complete area or section. Apply with a stainless smoothing trowel according to grain size, and then with a PVC or high-grade steel tool according to the desired structure. Wash tools in clean water immediately after use.

Technical data

EN 15824

Reaction to fire	B-s1, d0
Water absorption	W2
Water vapour permeability	V1
Thermal conductivity $\lambda_{10, \text{dry, mat}}$	0.7 W/(mK)
Grain size	2 mm

Material coverage

- 3.1 kg/m²
- approx. 8.1 m²/25 kg pail

The figures given here should be viewed as estimates. Actual values will depend on the evenness of the background and changes in plaster layer thickness. A trial application is recommended.

Working time

Working time: approx. 12 minutes/m²

Working temperature/climate

Do not use when air and/or wall temperatures are below +5°C. Protect fresh plaster from the effects of frost and rapid drying.

Method of delivery/storage

- 25 kg/pail
- Store up to 24 months in frost-free conditions (+5°C to +25°C).

Item code: 87268

AQUAPANEL®

▶ www.AQUAPANEL.com

@ aquapanel.info@knauf.com

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany.