



# **AQUAPANEL®**

## **Exterior Reinforcing Tape**

Glass fabric reinforcing tape with alkali-resistant coating



## Description

AQUAPANEL® Exterior Reinforcing Tape is used to reinforce joints in exterior walls where a coat of paint instead of render finish is to be applied on the AQUAPANEL® Exterior Basecoat or AQUAPANEL® Exterior Basecoat – white.

## Technical data

Weight/unit area	approx. 160 g/m <sup>2</sup>
Mesh size	4 x 4 mm
Initial tear strength	approx. 2200 N/5 cm
Thickness	approx. 0.5 mm
Width	20 cm
Length	50 m
Colour	blue

## Processing/application

Apply AQUAPANEL® Joint Filler – grey over the joints and embed AQUAPANEL® Exterior Reinforcing Tape.

## Material coverage

Approx. 2.1 m/m<sup>2</sup>

## Method of delivery/storage

20 cm wide rolls x 50 m long

5 rolls / bundle

150 rolls / pallet

Store in a dry place and protect from moisture.

Item code: 424086

**AQUAPANEL®**

[www.AQUAPANEL.com](http://www.AQUAPANEL.com)

[aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany