

Revision date: 15.04.2024  
Replacement of version 0028 of 13.07.2023

Version: 0029

# *Knauf Aquapanel GmbH & Co. KG*

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product identifier**

Trade name **AQUAPANEL® Board Primer**  
Product number **KAQ\_0437**  
Item code **49279, 73789**

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Appropriate use:  
The product is used as a primer/primer coating and as a layer to promote adhesion.

#### **Recommended restrictions on use:**

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.

### **1.3 Details of the supplier of the safety data sheet**

Knauf Aquapanel GmbH & Co. KG  
Zur Helle 11  
D-58638 Iserlohn

Telephone: +49-2374-50360

Fax: +49-2374-5036300

e-mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)

e-mail-address of the competent person responsible for this Safety Data Sheet:

[info@gefstoff.de](mailto:info@gefstoff.de)

#### **Technical contact:**

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn  
Telephone: +49-2374-50360 Fax: +49-2374-5036300

### **1.4 Emergency telephone number**

Giftnotruf der Charité - Universitätsmedizin Berlin, Campus Benjamin Franklin, Haus VIII (Wirtschaftsgebäude), UG  
Hindenburgdamm 30, 12203 Berlin  
**Giftnotruf Berlin +49-30-30686 700 (Advice in German and English)**  
**(24 hours, Monday – Sunday)**

## **SECTION 2: Hazards identification**

### **2.1 Classification of the substance or mixture**

The product contains sensitising substances in concentrations above one tenth of the specific concentration limit which leads to a classification of the mixture as skin sensitising.

The special labelling requirements of section 2.8 of Annex II of the Regulation must be applied.

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

### 2.2 Label elements

Hazard pictogram(s):	No pictogram
Signal word(s):	No signal word
Product identifier:	AQUAPANEL® Board Primer
Hazard statements:	Not required
Precautionary statements:	P102 Keep out of reach of children. P262 Do not get in eyes, on skin, or on clothing.

#### Supplemental hazard information:

EUH208	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

#### Special labelling in accordance with Article 58 (3)

of Regulation (EU) No 528/2012: Contains pyridine-2-thiol-1-oxide, sodium salt to ensure shelf life.

#### Remarks:

- The statement EUH210 must only appear on the label on the packaging of mixtures not intended for the general public.
- The precautionary statement P102 must only appear on the label of packaging supplied to the general public.

### 2.3 Other hazards

Preclude from exposure and handling this product those persons suffering from an allergy and those persons susceptible to respiratory disease.

The product is classified as slightly hazardous to water.

The mixture does not contain any substances classified as PBT/vPvB in a concentration of 0.1% or more.

The mixture does not contain substances having endocrine disrupting properties in accordance with Article 57 (f) of the Regulation (EC) No 1907/2006, Regulation (EU) No 2017/2100 or Regulation (EU) No 2018/605 in a concentration of 0.1% or more.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

REACH registration number:

The ingredients do not require registration according to Regulation (EC) No 1207/2006 [REACH] (exempted from registration or the annual tonnage does not require a registration).

#### Characterisation

This product is a mixture. It is a synthetic emulsion.

#### Substances presenting a health/environmental hazard within the meaning of Regulation (EC) No 1272/2008

CAS No	EC No	Identification	% by weight	Classification
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one	≥ 0.005 - < 0.05	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-factor: M = 1 M-factor (chronic): M = 1

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

(continued from 3.2 Mixtures)

CAS No	EC No	Identification	% by weight	Classification
55965-84-9	not available	reaction mass of 5-chloro-2-methyl-2 <i>H</i> -isothiazol-3-one and 2-methyl-2 <i>H</i> -isothiazol-3-one (3:1)	≥ 0.00015 – < 0.0015	Acute Tox. 3; H301 Acute Tox. 2; H310 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-factor: M = 100 M-factor (chronic): M = 100

See subsection 2.2 for further details. Full text of the hazard statements see Section 16.

**Substances for which there are Union workplace exposure limits (see also Section 8.)**

No substances.

**Additional information**

Specific concentration limits for 1,2-benzisothiazol-3(2*H*)-one in accordance with Annex VI of Regulation (EC) No 1272/2008:

Skin Sens. 1; H317:	C ≥ 0.05%	(valid until 31 August 2025)
Skin Sens. 1; H317:	C ≥ 0.036%	(it shall apply from 1 September 2025 at the latest)
ATE for 1,2-benzisothiazol-3(2 <i>H</i> )-one in accordance with Annex VI of Regulation (EC) No. 1272/2008:		
inhalation:	0.21 mg/L	(dusts or mists)
oral:	450 mg/kg bw	

Specific concentration limits for reaction mass of 5-chloro-2-methyl-2*H*-isothiazol-3-one and 2-methyl-2*H*-isothiazol-3-one (3:1) in accordance with Annex VI of Regulation (EC) No 1272/2008:

Eye Dam. 1; H318:	C ≥ 0.6%
Eye Irrit. 2; H319:	C ≥ 0.06 - < 0.6%
Skin Corr. 1C; H314:	C ≥ 0.6%
Skin Irrit. 2; H315:	C ≥ 0.06 - < 0.6%
Skin Sens. 1A; H317:	C ≥ 0.0015%

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information**

Take off contaminated clothing immediately and wash before reuse.  
Emergency eyewash should be provided in the immediate working surroundings.

**In case of inhalation**

Ensure supply of fresh air.

**In case of contact with skin**

In case of contact with skin wash off with soap and water.  
Do not try to remove product crusts from affected parts of the skin by force or by using solvents or thinner.  
By continuous complaints seek medical advice.

**In case of contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do.

**In case of ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting.  
Let water be swallowed in little sips (dilution effect). Put victim at rest. Take medical treatment.

### 4.2 Most important symptoms and effects, both acute and delayed

Possible allergic reaction in case of skin contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available.

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

## SECTION 5: Firefighting measures

### 5.1 *Extinguishing media*

#### **Suitable extinguishing media**

Product itself is non-combustible. Fire extinguishing method of surrounding areas must be discussed. Carbon dioxide, extinguishing powder, foam, water spray jet.

#### **Unsuitable extinguishing media**

Product itself is non-combustible. Fire extinguishing method of surrounding areas must be discussed.

### 5.2 *Special hazards arising from the substance or mixture*

In the event of fire the following can be released: carbon dioxide, carbon monoxide.

### 5.3 *Advice for firefighters*

Wear self-contained breathing apparatus. Do not inhale combustion gases.  
Collect contaminated firefighting water separately, must not be discharged into the drains.  
Cool endangered containers with water spray jet.

## SECTION 6: Accidental release measures

### 6.1 *Personal precautions, protective equipment and emergency procedures*

#### **For non-emergency personnel**

Ensure adequate ventilation. Use personal protective clothing.  
Keep away from unprotected people.

#### **For emergency responders**

For suitable fabric for personal protective clothing see Section 8.

### 6.2 *Environmental precautions*

Do not discharge into the drains, the aquatic environment and soil.

### 6.3 *Methods and material for containment and cleaning up*

Absorb with liquid-binding material (e.g. kieselguhr).  
Send in suitable containers for recovery or disposal.  
Clean contaminated floors and objects thoroughly with detergents, do not use solvents.  
Special danger of slipping by leaking/spilling product.

### 6.4 *Reference to other sections*

For personal protective equipment see also Section 8.  
For disposal considerations see also Section 13.

## SECTION 7: Handling and storage

### 7.1 *Precautions for safe handling*

#### **Advice on safe handling**

Ensure adequate ventilation.  
Comply with the minimum standards in accordance with TRGS 500<sup>1</sup>.  
Moreover, comply with the protective measures in accordance with TRGS 401<sup>1</sup>.  
In designing the work process the model solutions of the Control Guidance Sheet 120<sup>1</sup> must be taken into consideration in case of small-area skin contact (e.g. splashes) regardless on the duration of skin contact.  
In designing the work process the model solutions of the Control Guidance Sheet 120<sup>1</sup> must be taken into consideration in case of large-area skin contact (wetting of the skin) and short-term effect (duration of skin contact less than 15 minutes per shift).  
In designing the work process the model solutions of the Control Guidance Sheets 120<sup>1</sup> and 250<sup>1</sup> must be taken into consideration in case of large-area skin contact (wetting of the skin) and long-term effect (duration of skin contact more than 15 minutes per shift).

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

(continued from 7.1 Precautions for safe handling)

### Advice on general occupational hygiene

Avoid contact with eyes and skin. Take off contaminated clothing immediately and wash before reuse.  
At work do not eat, drink, smoke or take drugs.  
Wash hands before breaks and after work. Protect skin by using skin protective cream.  
Do not try to remove product crusts from affected parts of the skin by force or by using solvents or thinner.  
Set out skin protection guidelines.  
Emergency eyewash should be provided in the immediate working surroundings.

## 7.2 Conditions for safe storage, including any incompatibilities

### Advice on protection against fire and explosion

No special measures necessary.

### Requirements for storage rooms and vessels

Keep container tightly closed.

### Advice on storage compatibility

The information about joint storage given in Table 12 of TRGS 510<sup>1</sup> must be observed.

### Further information on storage conditions

Keep only in the original container.  
Protect from frost, intensive heat and direct sunlight.  
Do not store at temperatures below 5°C.  
Maximum period of storage (time): unopened storage life 18 months.

### Storage class (for Germany only)

LGK 12 in accordance with TRGS 510<sup>1</sup>.

## 7.3 Specific end use(s)

The product is only intended for the uses mentioned under subsection 1.2.  
Observe technical data sheet.  
In accordance with GISBAU (Information system of the German employers' liability insurance association for building and construction industry):  
GISCODE<sup>4</sup>: BSW20 (covering agents, water based)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

CAS number	Identification	Limit values	Remarks
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	0.05 mg/m <sup>3</sup> 0.2 mg/m <sup>3</sup> inhalable fraction* 0.2 mg/m <sup>3</sup> inhalable fraction  0.4 mg/m <sup>3</sup> inhalable fraction* 0.4 mg/m <sup>3</sup> inhalable fraction	<b>National limit values – eight hours</b> Austria Germany Switzerland  <b>National limit values – short-term</b> Germany Switzerland

\* Germany: This data is recommended by scientific experience and is not established law.

### DNEL values

#### Additional limit values for 1,2-benzisothiazol-3(2H)-one in accordance with the registration dossier:

worker, long-term exposition: inhalation, systemic effect: 6.81 mg/m<sup>3</sup>  
worker, long-term exposition: dermal, systemic effect: 0.966 mg/kg<sub>bw</sub>/d  
general population, long-term exposition: inhalation, systemic effect: 1.2 mg/m<sup>3</sup>  
general population, long-term exposition: dermal, systemic effect: 0.345 mg/kg<sub>bw</sub>/d

#### Additional limit values for reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) in accordance with the registration dossier:

worker, long-term exposition: inhalation, local effect: 0.02 mg/m<sup>3</sup>  
worker, short-term exposition: inhalation, local effect: 0.04 mg/m<sup>3</sup>  
general population, long-term exposition: inhalation, local effect: 0.02 mg/m<sup>3</sup>  
general population, short-term exposition: inhalation, local effect: 0.04 mg/m<sup>3</sup>  
general population, long-term exposition: oral, systemic effect: 0.09 mg/kg<sub>bw</sub>/d  
general population, short-term exposition: oral, systemic effect: 0.11 mg/kg<sub>bw</sub>/d

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

(continued from 8.1 Control parameters)

### PNEC values

#### Additional limit values for 1,2-benzisothiazol-3(2H)-one in accordance with the registration dossier:

aquatic, fresh water:	4.03 µg/l
aquatic, fresh water, intermittent release:	1.1 µg/l
aquatic, marine water:	0.403 µg/l
aquatic, marine water, intermittent release:	110 ng/l
aquatic, sewage treatment plant:	1.03 mg/l
sediment, fresh water:	49.9 µg/kg <sub>dw</sub>
sediment, marine water:	4.99 µg/kg <sub>dw</sub>
soil environment:	3 mg/kg <sub>dw</sub>

#### Additional limit values for reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) in accordance with the registration dossier:

aquatic, fresh water:	3.39 µg/l
aquatic, fresh water, intermittent release:	3.39 µg/l
aquatic, marine water:	3.39 µg/l
aquatic, marine water, intermittent release:	3.39 µg/l
aquatic, sewage treatment plant:	0.23 mg/l
sediment, fresh water:	0.027 mg/kg <sub>dw</sub>
sediment, marine water:	0.027 mg/kg <sub>dw</sub>
soil environment:	0.01 mg/kg <sub>dw</sub>

The methods for measuring chemical agents in workplace atmosphere must meet the general requirements of EN 481, EN 482 and EN 689.

## 8.2 Exposure controls

### Appropriate engineering controls

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See also subsection 7.1.

### Individual protection measures, such as personal protective equipment

Personal protective equipment needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer/supplier of the personal protective equipment.

#### Eye/face protection



Tightly fitting safety glasses in accordance with EN 166.  
In case of spraying: goggles.

#### Hand protection



Protective gloves made of natural latex, neoprene, nitrile rubber, PVC, butyl rubber, fluorinated rubber.  
Wear cotton undermitten if possible.  
The protective gloves to be used must be comply with the specifications of the standard EN 374.

#### Body protection

Closed work clothing. In case of spraying: single-use suit.

#### Respiratory protection



In case of spraying, higher concentrations and if ventilation insufficient, use a respiratory protection apparatus with respiration filter (particle filter P2).  
The limitations in wearing time according to the DGUV Regel 112-190<sup>2</sup> (rule of the German employers' liability insurance association) for the use of respirators have to observed.

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

(continued from 8.2 Exposure controls)

### Thermal hazards

Not relevant.

### Environmental exposure controls

See Section 6.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	liquid
Colour:	pink
Odour:	slight
Odour threshold:	no data available
Melting point/freezing point (°C):	0
Boiling point/initial boiling point/boiling range (°C):	100
Flammability:	not flammable
Lower explosion limit:	not applicable
Upper explosion limit:	not applicable
Flash point (°C), closed cup:	not applicable
Auto-ignition temperature (°C):	not applicable
Decomposition temperature (°C):	not determined
pH (as supplied):	8
Kinematic viscosity (mm <sup>2</sup> /s):	5454.545
Solubility in water:	completely miscible
Soluble in:	not determined
Partition coefficient: n-octanol/water (log value):	no data available
Vapour pressure (20°C) (hPa):	23
Density (g/cm <sup>3</sup> ) (20°C):	1.1
Relative vapour density (20°C):	not determined
Particle characteristics:	not applicable

### 9.2 Other information

None.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available for the product.

### 10.2 Chemical stability

The product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

When used as intended, no hazardous reaction known.

### 10.4 Conditions to avoid

When used as intended, no particular conditions known.

### 10.5 Incompatible materials

When used as intended, no particular materials known.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known. For hazardous combustion products see subsection 5.2.



Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product has not been tested.

#### Acute toxicity

LD50 rat, oral	(mg/kg)	450	(1,2-benzisothiazol-3(2H)-one)	(ATE)
		66	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 401)	
LC50 rat, inhalation	(mg/l/4h)	0.21	(1,2-benzisothiazol-3(2H)-one)	(ATE; dusts or mists)
		0.171	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 403)	
LD50 rat, dermal	(mg/kg)	> 2000	(1,2-benzisothiazol-3(2H)-one)	(OECD Test Guideline 402)
LD50 rabbit, dermal	(mg/kg)	> 141	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 402)	

#### Skin corrosion/irritation

Skin irritation, rabbit Corrosive Cat. 1C (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 404)

#### Serious eye damage/irritation

Eye irritation, rabbit Eye damage Cat. 1 (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 405)

#### Respiratory or skin sensitisation

The product has not been tested.

The product contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

These substances are classified as skin sensitising.

#### Germ cell mutagenicity

The mixture does not contain substances classified as germ cell mutagens.

#### Carcinogenicity

The mixture does not contain substances classified as carcinogenic.

#### Reproductive toxicity

The mixture does not contain substances classified as toxic for the reproduction.

#### Specific target organ toxicity (STOT)-single exposure

The mixture does not contain substances classified as being a specific target organ toxicant after single exposure.

#### Specific target organ toxicity (STOT)-repeated exposure

The mixture does not contain substances classified as being a specific target organ toxicant after repeated exposure.

#### Aspiration hazard

The mixture does not contain aspiration toxicants.

#### Symptoms related to the physical, chemical and toxicological characteristics

Possible allergic reaction in case of skin contact.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Persons suffering from an allergy may be sensitive to very low concentrations of allergenic substances and should consequently have no further contact with this product (possibility of an allergic reaction).

### 11.2 Information on other hazards

The mixture has not been tested.

#### Endocrine disrupting properties

The mixture does not contain substances having endocrine disrupting properties in accordance with Article 57 (f) of the Regulation (EC) No 1907/2006, Regulation (EU) No 2017/2100 or Regulation (EU) No 2018/605 in a concentration of 0.1% or more.

#### Other information

None.



Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

96 h LC50	(fish)	2.18 mg/l	(Oncorhynchus mykiss; rainbow trout) (1,2-benzisothiazol-3(2H)-one) (OECD Test Guideline 203)
		0.19 mg/l	(Oncorhynchus mykiss; rainbow trout) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (EPA OPP 72-1)
35 d NOEC	(fish)	≥ 46.4 µg/l	(Danio rerio; zebrafish) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 210)
48 h EC50	(daphnia)	2.94 mg/l	(Daphnia magna) (1,2-benzisothiazol-3(2H)-one) (OECD Test Guideline 202)
		0.16 mg/l	(Daphnia magna) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (EPA OPP 72-2)
21 d NOEC	(daphnia)	0.004 mg/l	(Daphnia magna) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 211)
72 h EC50	(algae)	70 µg/l	(Raphidocelis subcapitata) (1,2-benzisothiazol-3(2H)-one) (OECD Test Guideline 201)
		6.3 µg/l	(Skeletonema costatum) (reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 201)

#### Behaviour in sewage works:

When low concentrations are discharged correctly into adapted biological sewage treatment plants, disturbance of the degradation activity of activated sludge is not likely.

### 12.2 Persistence and degradability

The product can be largely eliminated from the water by abiotic processes, e.g. adsorption by activated sludge. Do not release into waterways untreated (biological sewage treatment plant).

- 1,2-benzisothiazol-3(2H)-one: 85%/63 d (OECD Test Guideline 301 C). Readily biodegradable.
  - Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1): 55.8%/28 d (OECD Test Guideline 301 B). Not readily biodegradable.
- Chemical oxygen demand (COD) No data available.  
 Biochemical oxygen demand (BOD5) No data available.  
 AOX-hint Not to apply.

### 12.3 Bioaccumulative potential

The product has not been tested.

Partition coefficient: n-octanol/water:

0.7	(20°C; pH 7)	(1,2-benzisothiazol-3(2H)-one) (EU method A.8)
0.326	(24°C)	(reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)) (OECD Test Guideline 107)

### 12.4 Mobility in soil

The product has not been tested.

### 12.5 Results of PBT and vPvB assessment

The mixture does not contain any substances classified as PBT/vPvB in a concentration of 0.1% or more.

### 12.6 Endocrine disrupting properties

The mixture does not contain substances having endocrine disrupting properties in accordance with Article 57 (f) of the Regulation (EC) No 1907/2006, Regulation (EU) No 2017/2100 or Regulation (EU) No 2018/605 in a concentration of 0.1% or more.

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

### 12.7 Other adverse effects

Ozone depletion potential	No data available.
Photochemical ozone creation potential	No data available.
Global warming potential	No data available.

The product is classified as slightly hazardous to water.

**Contains according to the formulation following compounds of directives 2006/11/EC and 80/68/EEC:**  
List II: Biocides and their derivatives not appearing in List I.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste disposal according to official state regulations.  
Consult the local waste disposal expert about waste disposal.  
Sewage disposal must be avoided.

#### Disposal operations/recovery operations according to Directive 2008/98/EC

Disposal operations:	D 9	Physico-chemical treatment
Recovery operations:	R 3	Recycling/reclamation of organic substances which are not used as solvents

#### Properties of waste which render it hazardous in accordance with Annex III of Directive 2008/98/EC

Not relevant.

#### Product/unused product

Waste disposal corresponding to European Waste Catalogue. Wastes must be classified with respect to their origin and depending on different processing steps.  
The waste codes mentioned as follows are only constituted as our recommendations.  
Referring to the particular case they should be completed or revised.

#### Dried-out product remainders:

EC waste code:	08 01 12
Waste notation:	Waste paint and varnish other than those mentioned in 08 01 11

#### Liquid product residues:

EC waste code:	08 01 20
Waste notation:	Aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

#### Alternative:

EC waste code:	17 09 04
Waste notation:	Mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

#### Contaminated packaging

Recommendation: Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Recommended cleansing agent:	Water.
Packaging that cannot be cleaned:	
EC waste code:	15 01 02
Waste notation:	Plastic packaging

## SECTION 14: Transport information

### 14.1 UN number or ID number

No dangerous good in accordance with the UN Model Regulations (ADR/RID/ADN/IMDG/ICAO/IATA).

### 14.2 UN proper shipping name

Not relevant.

### 14.3 Transport hazard class(es)

Not relevant.

### 14.4 Packing group

Not relevant.

**Safety data sheet in accordance with Regulation (EC) No 1907/2006**

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

**14.5 Environmental hazards**  
Not relevant.

**14.6 Special precautions for user**  
Not relevant.

**14.7 Maritime transport in bulk according to IMO instruments**  
Not relevant.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Information regarding relevant Union safety, health and environmental provisions**

- Conditions of restriction in accordance with Annex XVII Regulation (EC) No 1907/2006: None
- The mixture does not contain substances classified as substances of very high concern (SVHC) in accordance with Article 57 of the Regulation (EC) No 1907/2006 in a concentration of 0.1% or more.
- Directive 2010/75/EU: < 0.1% volatile organic compounds (VOC)
- Directive 2004/42/EC: Subcategory 1.1.h), type WB: binding primers  
Maximum VOC content limit value: 30 g/l  
Maximum content of the product in a ready to use condition: 1.0 g/l VOC

**Information regarding national laws/national measures that may be relevant (for Germany only)**

Indications on restriction of occupation:	Not relevant
Major Accident Ordinance:	Not relevant
Fire and explosion hazards:	Not relevant
Regulation on clean air (TA Luft):	Not relevant
Water hazard class:	WGK 1 – slightly hazardous to water (deduction of the WGK according to Annex 1 No 5.2 AwSV) <sup>3</sup> The German Ordinance on facilities for handling substances that are hazardous to water (AwSV) has to be observed
German Ordinance on Hazardous Substances (in accordance with EC-Directive 98/24/EC):	Articles 6, 7, 8 and 14 must be observed.
Technical Rules for Hazardous Substances <sup>1</sup> :	TRGS 400, 401, 500, 510, 555
Rules of the employers' liability insurance association <sup>2</sup> :	DGUV Regel 112-189, 112-190, 112-192, 112-195 DGUV Regel 100-500, chapter 2.29 (processing of coating material)
Classification in accordance with the easy-to-use workplace control scheme for hazardous substances of the Federal Institute for Occupational Safety and Health, version 2.2, 2014 <sup>3</sup> :	skin contact: hazard group HA

**15.2 Chemical safety assessment**  
No chemical safety assessment has been carried out for the mixture.

## SECTION 16: Other information

**Keeping (restrictions)** Article 8 paragraphs 5 and 6 of the German Ordinance on Hazardous Substances has to be observed. (only for Germany)

**Supply** to professional user, industrial user, to the general public

**Full text of the hazard statements referred to under sections 2 and 3 of the Safety Data Sheet**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

## Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Board Primer	Product number:	KAQ_0437
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

*(continued from Full text of the hazard statements referred to under sections 2 and 3 of the Safety Data Sheet)*

H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

### Key or legend to abbreviations and acronyms used in the safety data sheet

ADN:	Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ADR:	Accord relatif au transport international des marchandises dangereuses par route
AOX:	adsorbable organically bound halogens
ATE:	Acute Toxicity Estimates
AwSV:	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances that are hazardous to water)
bw:	body weight
CEPE:	Conseil Européen de l'Industrie des Peintures, des Encre d'Imprimerie et des Couleurs d'Arts (European Council of Paint, Printing Ink and Artist's Colours Industry)
DGUV:	Deutsche Gesetzliche Unfallversicherung (German Social Accident Insurance)
DNEL:	Derived No-Effect Level
EPA:	United States Environmental Protection Agency
ICAO/IATA:	International Civil Aviation Organisation/International Air Transport Association-Dangerous Goods Regulations
IMDG-Code:	International Maritime Dangerous Goods-Code
IMO:	International Maritime Organization
LGK:	Lagerklasse (storage class)
NOEC:	No Observed Effect Level Concentration
OECD:	Organisation for Economic Co-operation and Development
OPP:	EPA's Office of Pesticide Programs
PBT:	persistent, bioaccumulative and toxic
PNEC:	Predicted No-Effect Concentration
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer
TRGS:	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
VCI:	Verband der chemischen Industrie (German Association of Chemical Industry)
vPvB:	very persistent and very bioaccumulative

### Literature references and sources for data

- <https://www.baua.de>
- <https://www.arbeitssicherheit.de>
- <https://www.umweltbundesamt.de>
- <https://www.wingisonline.de>
- <https://www.baua.de/emkg>

### Method used for the classification of the mixture

The classification was undertaken in accordance with the classification criteria of Annex I of Regulation (EC) No 1272/2008.

### Changes which have been made to the previous version of the safety data sheet

Revised sections: 3.2, 11.1, 12.1, 15.1, 16, headers

**The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.**

Compiled by: **Dr. Michael Urban**  
**Fachberatung Gefahrstoff Gefahrgut**  
Vogelbeerweg 3 D-26180 Rastede-Ipwege / Germany  
Tel.: +49-4402-695620 Fax: +49-4402-695621