

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Revision date: 15.04.2024
Replacement of version 0027 of 24.05.2023

Version: 0028

Knauf Aquapanel GmbH & Co. KG

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 *Product identifier*

Trade name **AQUAPANEL® Exterior Basecoat**
Product number **KAQ_0409**
Item code **49157**

Unique formula identifier (UFI) in accordance with section 5 of Part A of Annex VIII to Regulation (EC) No 1272/2008:
UFI: GV00-70P0-S00N-FVJT

1.2 *Relevant identified uses of the substance or mixture and uses advised against*

Appropriate use:
The product is used as a basecoat.

Recommended restrictions on use:

People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

1.3 *Details of the supplier of the safety data sheet*

Knauf Aquapanel GmbH & Co. KG
Zur Helle 11
D-58638 Iserlohn

Telephone: +49-2374-50360 Fax: +49-2374-5036300
e-mail: aquapanel.info@knauf.com

e-mail-address of the competent person responsible for this Safety Data Sheet:
info@gefstoff.de

Technical contact:

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn
Telephone: +49-2374-50360 Fax: +49-2374-5036300

1.4 *Emergency telephone number*

Giftnotruf der Charité - Universitätsmedizin Berlin, Campus Benjamin Franklin, Haus VIII (Wirtschaftsgebäude), UG
Hindenburgdamm 30, 12203 Berlin
Giftnotruf Berlin +49-30-30686 700 (Advice in German and English)
(24 hours, Monday – Sunday)

SECTION 2: Hazards identification

2.1 *Classification of the substance or mixture*

Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H335

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name: AQUAPANEL® Exterior Basecoat Product number: KAQ_0409
Company/Undertaking: Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn
Telephone: +49-(0)2374-50360 Revision date: 15.04.2024

2.2 Label elements

Hazard pictogram(s):



Signal word(s):

Danger

Product identifier:

AQUAPANEL® Exterior Basecoat
contains Portland cement clinker, Flue dust, Portland cement, calcium hydroxide

Hazard statements:

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements:

P102 Keep out of reach of children.
P261 Avoid breathing dust.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
P302 + P352 IF ON SKIN: Wash with plenty of water and soap.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
P501 Dispose of contents/container to hazardous or special waste collection point.

Supplemental hazard information: Not required

Remarks:

- According to Article 35 paragraph 2 of Regulation (EC) No 1272/2008 packaging supplied to the general public should not have either a shape or form to mislead consumers.
- The use of the precautionary statements P102 and P501 is necessary for the labelling of the dangerous mixture supplied to the general public.

2.3 Other hazards

Prolonged and repetitive contact with the skin or contact with moist skin can lead to contact dermatitis.

Cement may irritate the throat and respiratory tract.

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of damage to the lungs.

The cement used in this product is low in chromate by reducing the content of sensitising chromium VI to below 2 ppm in the cement ready for use in this product. The effectiveness of the chromate reduction depends on the appropriate storage and observing the shelf life (see also subsection 7.2).

Quartz is known to be a silicosis-producing substance to human.

Avoid absolutely formation of dust during processing and treatment.

The product is classified as slightly hazardous to water.

In case of ingress of water formation of a strong alkaline solution.

The mixture does not contain any substances classified as PBT/vPvB or any substances having endocrine disrupting properties in concentrations of more or equal than 0.1%.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Basecoat	Product number:	KAQ_0409
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

REACH registration number:
 Flue dust, Portland cement: 01-2119486767-17-XXXX
 Calcium hydroxide: 01-2119475151-45-XXXX

Characterisation

This product is a mixture. It is a dry mortar based on special cements (low in chromium VI), loading material (quartz sand, hydrate of white lime), thickening agents (cellulose ether) and copolymers based on vinyl chloride, ethylene and vinyl esters.

Substances presenting a health/environmental hazard within the meaning of Regulation (EC) No 1272/2008

CAS No	EC No	Identification	% by weight	Classification
65997-15-1	266-043-4	Portland cement clinker	15 - 25	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Eye Dam. 1; H318 STOT SE 3; H335
1305-62-0	215-137-3	calcium hydroxide	5 - 10	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335
68475-76-3	270-659-9	flue dust, Portland cement	> 0.02 - < 1	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 STOT SE 3; H335

See subsection 2.2 for further details. Full text of the hazard statements see Section 16.

Substances for which there are Union workplace exposure limits (see also Section 8.)

The product contains quartz in concentrations > 45 - < 55%.
 The content of the respirable dust fraction is less than 1%.

Additional information

The hazardous properties of the product indicated by the classification occur in case of contact with moisture or water (alkaline reaction of Portland cement and calcium hydroxide).
 The type of the Portland cement used in this product is reduced in chromate. For cements treated with a chromium VI reducing agent, the effectiveness of the reducing agent diminishes with time.
 Therefore, packaging of cement-containing mixtures contain information on the period of time (shelf-life) for which the manufacturer has established that the reducing agent will continue to maintain the level of soluble chromium VI below the imposed limit of 0.0002%. In case of improper storage (ingress of moisture) or exceeding the shelf life the reducing agent can lose its effectiveness prematurely and a sensitising effect of the cement on the skin cannot be ruled out.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing immediately and wash before reuse.
 In the immediate working surroundings emergency eye wash must be installed. Label its location conspicuously.

In case of inhalation

Take affected person to fresh air. Dust in throat and nasal passages must be removed immediately.
 By continuous complaints seek medical advice.

In case of contact with skin

In case of contact with skin wash off immediately with plenty of water.
 By continuous complaints seek medical advice.

In case of contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do.
 Do not rub eyes, cornea damage is possible by mechanical stress.

Trade name: AQUAPANEL® Exterior Basecoat

Product number: KAQ_0409

Company/Undertaking: Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn

Telephone: +49-(0)2374-50360

Revision date: 15.04.2024

(continued from 4.1 Description of first aid measures)

In case of ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Let water be swallowed in little sips (dilution effect). Do not induce vomiting.
Take medical treatment immediately.

4.2 Most important symptoms and effects, both acute and delayed

After inhalation: coughing, sore throat.
After ingestion: abdominal pains.
After contact with skin: redness, dry skin.
After contact with eyes: serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Product itself is non-combustible. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Product itself is non-combustible. Co-ordinate fire-fighting measures to the fire surroundings.

5.2 Special hazards arising from the substance or mixture

No particular hazards known.

5.3 Advice for firefighters

Use self-contained breathing apparatus in dust-laden atmosphere.
Collect contaminated firefighting water separately (strong alkaline solution) and dispose of in accordance with the local regulations. Classification of fire reaction rating as per EN 13501-1: Euro class A1 (Non-combustible).

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid dust formation. Use personal protective clothing. Keep away from unprotected people.

For emergency responders

For suitable fabric for personal protective clothing see Section 8.

6.2 Environmental precautions

Do not discharge into the drains, the aquatic environment and soil.

6.3 Methods and material for containment and cleaning up

Keep away from water. Pick up mechanically. Avoid raising dust.
Do not use compressed air for cleaning surfaces or clothing.
Approved industrial vacuum cleaners or central suction systems should be used for removal of dry product.
Clean up wet product and place in a container. Allow material to dry and solidify before disposal.
Dispose of absorbed material in accordance with the regulations.
After contact with water product is setting up.
Clear contaminated areas thoroughly.

6.4 Reference to other sections

For personal protective equipment see also Section 8.
For disposal considerations see also Section 13.

Trade name:	AQUAPANEL® Exterior Basecoat	Product number:	KAQ_0409
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid formation of dust. Provide good ventilation of working area (local exhaust ventilation if necessary).
Keep sampling device dry. Always close containers tightly after the removal of product.
Dust deposits that cannot be avoided must be taken up regularly.
For bagged mortar used in open-ended mixers, first add the water and then carefully add the mortar.
Keep the height of fall low. Start stirring slowly.
Do not compress empty bags, except when contained in another clean bag.
When working, do not kneel in fresh mortar. Use only alkali-proof equipment (alkaline reaction after water supply).
The hazardous properties of the product indicated by the classification occur in case of addition of water.
Avoid contact with skin and eyes. Comply with the minimum standards in accordance with TRGS 500¹.
Moreover, comply with the protective measures in accordance with TRGS 401¹.
In case of release of mineral dust, comply with the protective measures in accordance with TRGS 559¹.

Inhalation:

In designing the work process the model solutions of the Control Guidance Sheets 100¹, La-101¹ and 110¹ must be taken into consideration in case of possible release of dust and only small amounts of product (range of grams).
In designing the work process the model solutions of the Control Guidance Sheets 200¹, 208¹ and 240¹ must be additionally taken into consideration in case of possible release of dust and medium amounts of product (range of kilograms).
In designing the work process the model solutions of the Control Guidance Sheet 300¹ (closed system) must be taken into consideration in case of possible release of dust and large amounts of product (range of tons).
The consideration of the Good Practice Guide on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it⁴ is recommended.

Skin contact:

In designing the work process the model solutions of the Control Guidance Sheet 120¹ must be taken into consideration in case of small-area skin contact (e.g. splashes) and short-term effect (duration of skin contact less than 15 minutes per shift). In case of long-term effect (duration of skin contact more than 15 minutes per shift), the model solutions of the Control Guidance Sheet 250¹ must be additionally taken into consideration.
In designing the work process the model solutions of the Control Guidance Sheets 120¹ and 250¹ must be taken into consideration in case of large-area skin contact (wetting of the skin) and regardless on the duration of skin contact.

Advice on general occupational hygiene

Do not inhale dust. Avoid contact with eyes and skin. At work do not eat, drink, smoke or take drugs.
Take off contaminated clothing immediately and wash before reuse. Store work clothing separately.
After worktime and before breaks the affected skin areas must be thoroughly cleaned.
After work protect skin by using skin protective cream. Set out skin protection guidelines.
In the immediate working surroundings emergency eye wash must be installed. Label its location conspicuously.

7.2 Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

No special measures necessary.

Requirements for storage rooms and vessels

Keep in the original container and tightly closed. Store container in a well-ventilated place.
Do not store in aluminium containers. Risk of corrosion when moisture is present.
For cements treated with a chromium VI reducing agent, the effectiveness of the reducing agent diminishes with time. Therefore, packaging of cement-containing mixtures contain information on the period of time (shelf-life) for which the manufacturer has established that the reducing agent will continue to maintain the level of soluble chromium VI below the imposed limit of 0.0002%. They also indicate the appropriate storage conditions for maintaining the effectiveness of the reducing agent.
In case of improper storage (ingress of moisture) or exceeding the shelf life the reducing agent can lose its effectiveness prematurely and a sensitising effect of the cement on the skin cannot be ruled out.

Advice on storage compatibility

Do not store together with acids. Store apart from oxidising agents and explosible agents.
The information about joint storage given in Table 12 of TRGS 510¹ must be observed.

Further information on storage conditions

Store in a dry place. Protect from wetness.
Maximum period of storage (time): unopened storage life 6 months.

Storage class (for Germany only)

LGK 13 in accordance with TRGS 510¹.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name: AQUAPANEL® Exterior Basecoat	Product number: KAQ_0409
Company/Undertaking: Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn	
Telephone: +49-(0)2374-50360	Revision date: 15.04.2024

7.3 Specific end use(s)

The product is only intended for the uses mentioned under subsection 1.2. Observe technical data sheet.
 In accordance with GISBAU (Information system of the German employers' liability insurance association for building and construction industry):
 GISCODE⁵: ZP 1 (products containing cement, low in chromium)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

CAS number	Identification	Limit values	Remarks
65997-15-1	Portland cement	5 mg/m ³ inhalable aerosol 1 mg/m ³ respirable fraction 5 mg/m ³ inhalable fraction 1 mg/m ³ respirable fraction 10 mg/m ³ 1 mg/m ³ respirable fraction 6 mg/m ³ 6 mg/m ³ inhalable fraction 2 mg/m ³ respirable fraction 4 mg/m ³ respirable fraction 5 mg/m ³ inhalable aerosol 10 mg/m ³ inhalable fraction 4 mg/m ³ respirable fraction 10 mg/m ³ inhalable aerosol	National limit values – eight hours Austria Belgium Finland Finland Hungary Ireland Latvia Poland Poland Spain Switzerland United Kingdom United Kingdom National limit values – short-term Austria
14808-60-7	quartz	0.1 mg/m ³ respirable fraction 0.05 mg/m ³ respirable fraction 0.1 mg/m ³ respirable dust 0.3 mg/m ³ inhalable aerosol 0.1 mg/m ³ respirable aerosol 0.05 mg/m ³ respirable fraction 0.05 mg/m ³ assessment standard* respirable fraction 0.3 mg/m ³ inhalable fraction 0.05 mg/m ³ respirable fraction 0.15 mg/m ³ respirable aerosol 0.075 mg/m ³ respirable fraction 0.6 mg/m ³ inhalable aerosol 0.2 mg/m ³ respirable aerosol 0.4 mg/m ³ assessment standard* respirable fraction	EU-exposure limit value in accordance with Directive (EU) 2019/130 eight hours Different national limit values – eight hours Austria Belgium Denmark Denmark Finland Germany Norway Spain Switzerland The Netherlands Different national limit values – short_term Denmark Denmark Germany

Trade name: AQUAPANEL® Exterior Basecoat

Product number: KAAQ_0409

Company/Undertaking: Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn

Telephone: +49-(0)2374-50360

Revision date: 15.04.2024

(continued from 8.1 Control parameters)

CAS number	Identification	Limit values	Remarks
1305-62-0	calcium hydroxide	1 mg/m ³ (respirable fraction) 4 mg/m ³ (respirable fraction) 1 mg/m ³ inhalable fraction 1 mg/m ³ inhalable fraction 2 mg/m ³ inhalable fraction 1 mg/m ³ inhalable fraction 4 mg/m ³ inhalable fraction 2 mg/m ³ 2 mg/m ³ inhalable fraction 6 mg/m ³ inhalable fraction	EU-exposure limit value in accordance with Directive (EU) 2017/164 eight hours short term Different national limit values – eight hours Austria Germany Poland Switzerland Different national limit values – short term Austria Denmark Germany Poland

* The assessment standard has been fixed in accordance with TRGS 559. It must be taken into account for the risk assessment and the control of the effectiveness of the preventive measures. This standard value must be fallen below.

DNEL values

Additional limit values for calcium dihydroxide in accordance with the registration dossier:

worker, short-term exposition: inhalation, local effect:	4 mg/m ³
worker, long-term exposition: inhalation, local effect:	1 mg/m ³
general population, short-term exposition: inhalation, local effect:	4 mg/m ³
general population, long-term exposition: inhalation, local effect:	1 mg/m ³

PNEC values

Additional limit values for calcium dihydroxide in accordance with the registration dossier:

aquatic, fresh water:	0.49 mg/l
aquatic, fresh water, intermittent release:	0.49 mg/l
aquatic, marine water:	0.32 mg/l
aquatic, sewage treatment plant:	3 mg/l
soil environment:	1080 mg/kg _{dw}

The methods for measuring chemical agents in workplace atmosphere must meet the general requirements of EN 481, EN 482 and EN 689.

8.2 Exposure controls

Appropriate engineering controls

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See also subsection 7.1.

In case of dust formation exhaust ventilation at the object (initiation point) is necessary.

In case of release of dust, additionally comply with the protective measures in accordance with TRGS 559¹.

The effectiveness of suitable protective measures must be controlled.

Suitable assessment methods are described in the German TRGS 402¹.

Individual protection measures, such as personal protective equipment

Personal protective equipment needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer/supplier of the personal protective equipment.

Eye/face protection



Tightly fitting safety glasses in accordance with EN 166 (in case of dust formation and and splashing).

(continued from 8.2 Exposure controls)

Hand protection



Cotton gloves (nitrile-coated) marked with a CE sign. Wear cotton undermitten if possible. Suitable gloves for the handling of products containing cement, low in chromium (GISCODE⁵: ZP 1) in accordance with GISBAU (Information system of the the German professional associations for building and construction industry):

- ANSELL: Flexitrit L27, Fleximax 27 or 35, Hylite, Nitrotough N210, Sol-Knit
- Ampri: SolidSafety Cut 081101, SolidSafety Tough 081201, SolidSafety Tough Dots 081202
- KCL: Sahara, Gobi, Nitex
- MAPA: Stansolv AK 22, Duo-Mix 405, Enduro 328, Titanlite 397, Titansuperlite
- UVEX: uvex Profi Ergo XG 20, uvex phynomic pro

The protective gloves to be used must be comply with the specifications of the standard EN 374.

Body protection

Closed work clothing.

Respiratory protection



In dust-laden atmosphere: breathing apparatus with particle filter P2 or filtering half mask to protect against particles FFP1 – FFP3 in accordance with EN 149.

Maximum use concentration for substances with occupational exposure limit values (OELV):

P1-filter up to max. 4 x OELV;

P2-filter up to max. 10 x OELV;

P3-filter up to max. 30 x OELV.

These values are only valid for Germany in accordance with the German DGUV Regel 112-190². The limitations in wearing time according to the DGUV Regel 112-190² (rule of the German employers' liability insurance association) for the use of respirators have to be observed.

Thermal hazards

Not relevant.

Environmental exposure controls

See Section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	solid (powder)
Colour:	grey
Odour:	odourless
Odour threshold:	no data available
Melting point/freezing point (°C):	not determined
Boiling point/initial boiling point/boiling range (°C):	not determined
Flammability:	Euro class A1 (Non-combustible) (DIN EN 13501-1)
Lower explosion limit:	not applicable
Upper explosion limit:	not applicable
Flash point (°C), closed cup:	not applicable
Auto-ignition temperature (°C):	not applicable
Decomposition temperature (°C):	580 (decomposition of calcium hydroxide)
pH (mixed with water):	11.5 – 13
Kinematic viscosity (mm ² /s):	not applicable
Solubility in water (at 20°C):	1650 mg/l (calcium hydroxide)
Soluble in:	no data available
Partition coefficient: n-octanol/water (log value):	not applicable
Vapour pressure (20°C) (mbar):	not applicable
Bulk density (g/cm ³):	0.9 – 1.5
Relative vapour density (20°C):	not applicable
Particle characteristics:	powdery

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Basecoat	Product number:	KAQ_0409
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

9.2 Other information

None.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available for the product.

10.2 Chemical stability

The product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Wet product reacts with aluminium under the formation of hydrogen.

Reaction of moist cement with acids, ammonium salts, aluminium and other base metals.

Cement is soluble in hydrofluoric acid to form toxic and corrosive silicon tetrafluoride gas.

10.4 Conditions to avoid

Avoid influence of moisture before processing (alkaline reaction with water).

Decomposition of calcium hydroxide into calcium oxide and water at temperatures above 580°C.

10.5 Incompatible materials

Calcium hydroxide contained in this product reacts with acids under the formation of calcium salts.

Wet product reacts with aluminium under the formation of hydrogen.

Reaction of moist cement with acids, ammonium salts, aluminium and other base metals.

Cement is soluble in hydrofluoric acid to form toxic and corrosive silicon tetrafluoride gas.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

For hazardous combustion products see subsection 5.2.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has not been tested.

The toxicological data mentioned are derived from an analogous product.

Acute toxicity

LD50 rat, oral	(mg/kg)	> 2000	(calcium dihydroxide) (OECD Test Guideline 425)
LC50 rat, inhalation	(mg/l/4h)	> 6.04	(calcium dihydroxide) (OECD Test Guideline 436)
LD50 rabbit, dermal	(mg/kg)	> 2500	(calcium dihydroxide) (OECD Test Guideline 402)

Skin corrosion/irritation

Skin Irrit. 2: Causes skin irritation.

Irritant effect on skin (rabbit) Irritating Cat. 2 (calcium dihydroxide) (OECD Test Guideline 404)

Serious eye damage/irritation

Eye Dam. 1: Causes serious eye damage.

Irritant effect on eyes (rabbit) Eye damage Cat. 1 (calcium dihydroxide) (OECD Test Guideline 405)

Respiratory or skin sensitisation

The product contains cement reduced in chromate with a content of soluble chromium less than 2 ppm related to the cement portion. There is only a very little risk to fall ill with bricklayer's itch. Yet a sensitisation by skin contact cannot be ruled out for persons who are very sensitive.

Germ cell mutagenicity

The mixture does not contain substances classified as germ cell mutagens.

Carcinogenicity

The mixture does not contain substances classified as carcinogenic.

Reproductive toxicity

The mixture contains a substance classified as toxic for the reproduction below the generic cut-off value.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Basecoat	Product number:	KAQ_0409
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

(continued from 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008)

Specific target organ toxicity (STOT)-single exposure

STOT SE 3: May cause respiratory irritation.

Specific target organ toxicity (STOT)-repeated exposure

The mixture does not contain substances classified as being a specific target organ toxicant after repeated exposure.

Aspiration hazard

The mixture does not contain aspiration toxicants.

Symptoms related to the physical, chemical and toxicological characteristics

After inhalation: coughing, sore throat.

After ingestion: abdominal pains.

After contact with skin: redness, dry skin.

After contact with eyes: serious eye damage.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

The product contains cement reduced in chromate with a content of soluble chromium less than 2 ppm related to the cement portion. There is only a very little risk to fall ill with bricklayer's itch. Yet a sensitisation by skin contact cannot be ruled out for persons who are very sensitive.

Prolonged and repetitive contact with the skin or contact with moist skin can lead to contact dermatitis.

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of damage to the lungs. Quartz is known to be a silicosis-producing substance to human.

11.2 Information on other hazards

The mixture has not been tested.

Endocrine disrupting properties

The mixture does not contain substances having endocrine disrupting properties in accordance with Article 57 (f) of the Regulation (EC) No 1907/2006 in a concentration of 0.1% or more.

Other information

None.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

96 h LC50	(fish)	50.6 mg/l	(Oncorhynchus mykiss: rainbow trout) (calcium hydroxide) (OECD Test Guideline 203)
48 h EC50	(daphnia)	49.1 mg/l	(Daphnia magna) (calcium hydroxide) (OECD Test Guideline 202)
72 h EC50	(algae)	184.57 mg/l	(Raphidocelis subcapitata) (calcium hydroxide) (OECD Test Guideline 201)

Behaviour in sewage works:

Due to the alkaline character of the product, usually, it has to be neutralised before contaminated effluents are introduced into the waste water treatment system.

12.2 Persistence and degradability

Chemical oxygen demand (COD)	No data available.
Biochemical oxygen demand (BOD5)	No data available.
AOX-hint	Not to apply

12.3 Bioaccumulative potential

The product has not been tested.

12.4 Mobility in soil

The product has not been tested.

12.5 Results of PBT and vPvB assessment

The mixture does not contain any substances classified as PBT/vPvB in a concentration of 0.1% or more.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name: AQUAPANEL® Exterior Basecoat Product number: KAQ_0409
Company/Undertaking: Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn
Telephone: +49-(0)2374-50360 Revision date: 15.04.2024

12.6 Endocrine disrupting properties

The mixture does not contain substances having endocrine disrupting properties in accordance with Article 57 (f) of the Regulation (EC) No 1907/2006 in a concentration of 0.1% or more.

12.7 Other adverse effects

Ozone depletion potential Not relevant
Photochemical ozone creation potential Not relevant
Global warming potential Not relevant

The product is classified as slightly hazardous to water.

In case of ingress of water formation of a strong alkaline solution.

Increase of pH-value possible after release of large amounts into the aquatic environment.

Contains according to the formulation following compounds of directives 2006/11/EC and 80/68/EEC:

None.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste disposal according to official state regulations.

Sewage disposal must be avoided.

Consult the local waste disposal expert about waste disposal.

Disposal operations/recovery operations according to Directive 2008/98/EC

Disposal operations: D 9 Physico-chemical treatment
Recovery operations: R 5 Recycling/reclamation of other inorganic materials

Properties of waste which render it hazardous in accordance with Annex III of Directive 2008/98/EC

HP 4: Irritant
HP 5: Specific Target Organ Toxicity (STOT)

Product/unused product

Waste disposal corresponding to European Waste Catalogue. Wastes must be classified with respect to their origin and depending on different processing steps. The waste codes mentioned as follows are only constituted as our recommendations. Referring to the particular case they should be completed or revised.

Dried-out product remainders:

EC waste code: 17 01 01
Waste notation: Concrete

Unused product:

EC waste code: 17 01 06
Waste notation: Mixtures of, or separate fractions of concrete, bricks, tiles and ceramics containing hazardous substances

Contaminated packaging

Recommendation: Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Recommended cleansing agent: Immediately clean with water.
Hardened product can only be removed mechanically.

Packaging that cannot be cleaned:

EC waste code: 15 01 10
Waste notation: Packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in accordance with the UN Model Regulations (ADR/RID/ADN/IMDG/ICAO/IATA).

14.2 UN proper shipping name

Not relevant.

14.3 Transport hazard class(es)

Not relevant.

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Basecoat	Product number:	KAQ_0409
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

14.4 *Packing group*

Not relevant.

14.5 *Environmental hazards*

Not relevant.

14.6 *Special precautions for user*

Not relevant.

14.7 *Maritime transport in bulk according to IMO instruments*

Not relevant.

SECTION 15: Regulatory information

15.1 *Safety, health and environmental regulations/legislation specific for the substance or mixture*

Information regarding relevant Union safety, health and environmental provisions

- Conditions of restriction in accordance with Annex XVII Regulation (EC) No 1907/2006: Annex XVII, point 47 (Chromium VI compounds)
- The mixture does not contain substances classified as substances of very high concern (SVHC) in accordance with Article 57 of the Regulation (EC) No 1907/2006 in a concentration of 0.1% or more.
- Obligation of notification in accordance with Annex VIII to Regulation (EC) No 1272/2008.
Number of the product in the Poison Information Database: 7611117
(BfR number; German Federal Institute of Risk Assessment)
- Observe Directive 2003/53/EC.
- Observe employment restrictions under the law for the protection of young people at work (94/33/EC).
- Observe Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Information regarding national laws/national measures that may be relevant (for Germany only)

Restriction of occupation:	Youth Employment Protection Act must be observed
Major Accident Ordinance:	Not relevant
Fire and explosion hazards:	Not relevant
Regulation on clean air (TA Luft):	Number 5.2.1
Fire and explosion hazards:	Not relevant
Water hazard class:	WGK 1 – slightly hazardous to water (deduction of the WGK according to Annex 1 No 5.2 AwSV) ³ The German Ordinance on facilities for handling substances that are hazardous to water (AwSV) has to be observed.

German Ordinance on Hazardous Substances

(in accordance with EC-Directive 98/24/EC):

Regulation on Occupational Medical Prevention (ArbMedVV):

Articles 6, 7, 8, 9, 14, Annex I No 2 must be

Annex, Part 1 (1):

Obligatory prophylaxis: The employer shall arrange occupational medical prophylaxis for workers conducting activities with exposure to inhalable dust, if the occupational exposure limit value is exceeded.

Annex, Part 1 (2):

Prophylaxis offer: For activities involving inhalable dust occupational medical prevention has to be offered.

DGUV Recommendations on Occupational Medical Prevention: dust exposure

Technical Rules for Hazardous Substances¹:

TRGS 400, 401, 402, 500, 510, 555, 559, 600, 900

Rules of the employers' liability insurance association²:

DGUV Regel 112-189, 112-190, 112-192, 112-195

Classification in accordance with the easy-to-use workplace control scheme for hazardous substances of the Federal

Institute for Occupational Safety and Health, version 2.2, 2014⁶: inhalation:

hazard group B

skin contact: hazard group HB

(in case of release of mineral dust, the protective measures in accordance with TRGS 559¹ should be applied preferably)

Safety data sheet in accordance with Regulation (EC) No 1907/2006

Trade name:	AQUAPANEL® Exterior Basecoat	Product number:	KAQ_0409
Company/Undertaking:	Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn		
Telephone:	+49-(0)2374-50360	Revision date:	15.04.2024

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for the mixture.

SECTION 16: Other information

Keeping (restrictions) Article 8 paragraphs 5 and 6 of the German Ordinance on Hazardous Substances has to be observed. (only for Germany)

Supply to professional user, industrial user

Full text of the hazard statements referred to under sections 2 and 3 of the Safety Data Sheet

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Key or legend to abbreviations and acronyms used in the safety data sheet

ADN:	Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ADR:	Accord relatif au transport international des marchandises dangereuses par route
AOX:	adsorbable organically bound halogens
AwSV:	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances that are hazardous to water)
DGUV:	Deutsche Gesetzliche Unfallversicherung (German Social Accident Insurance)
DNEL:	Derived No-Effect Level
ICAO/IATA:	International Civil Aviation Organisation/International Air Transport Association-Dangerous Goods Regulations
IMDG-Code:	International Maritime Dangerous Goods-Code
IMO:	International Maritime Organization
LGK:	Lagerklasse (storage class)
NEPSI:	Noyau Européen pour la Silice – European Network for Silica
OECD:	Organisation for Economic Co-operation and Development
PBT:	persistent, bioaccumulative and toxic
PNEC:	Predicted No-Effect Concentration
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer
RTECS:	Registry of Toxic Effects of Chemical Substances
TRGS:	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
vPvB:	very persistent and very bioaccumulative

Literature references and sources for data

- <https://www.baua.de>
- <https://www.arbeitssicherheit.de>
- <https://www.umweltbundesamt.de>
- <https://www.nepsi.eu>
- <https://www.wingis-online.de>
- <https://www.baua.de/emkg>

Method used for the classification of the mixture

The classification was undertaken in accordance with the classification criteria of Annex I of Regulation (EC) No 1272/2008.

Changes which have been made to the previous version of the safety data sheet

Revised sections: 2.3, 8.1, 11.1, 12.7, 15.1, headers

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Compiled by:

Dr. Michael Urban

Fachberatung Gefahrstoff Gefahrgut

Vogelbeerweg 3

D-26180 Rastede-Ipwege / Germany

Tel.: +49-4402-695620

Fax: +49-4402-695621